

## Model : TGM 18.240 4X2 BB

### Technical extent of delivery

Code	Customer Special Request	Designation
000AA		Non-variable parts
001AC		steering arrangement, right
005BJ		Wheelbase 3575 mm
006EV		rear frame overhang 1125 mm
018MK		D0836LFL40 engine - 240 hp/176 kW EURO 3 - 925 Nm Common Rail
02AAB		instrument panel kmh 'Base-Line'
022SF		gearbox ZF 12 AS 1210 OD MAN TipMatic
023FT		fuel tank 150l right
025MU		front axle VOK-07 dropped
026EA		front springs parabolic 7.1 t
027AC		radiator and intercooler
028EB		rear springs parabolic, 11.5 t
03KAA		fuel tank fitted
030AC		hydraulic steering
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034NH		hypoid rear axle HY-1133
035FE		Hypoid axle ratio i = 5.29
037AC		with differential lock in rear axle
038GC		disc wheels 10 hole 8.25-22.5 on 1stFA TL
038PC		disc wheels 10-hole 8.25-22.5 on 1stRA TL
038TC		disc wheel 10-hole 8.25-22.5 as spare wheel TL
042XY		without electronic tachograph
050NK		C cab 2240mm wide, 1620mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality
058NH		driver's seat, high-comfort, with air suspension
059HC		Static co-driver's seat with storagebox
064AC		two additional vehicle keys
080AE		door interior panelling washable
116AE		visco fan
118MA		EDC engine regulation
121EH		neutral pos. switch
123CC		strainer for fuel tank
123CE		chain for tank cap
124AL		fuel filter
124AR		additional fuel filter heated with water trap, make SEPAR
124EA		fuel filter heating

142AF		calibrate tachograph
153KC		air conditioning system AC R134A with automatic temperature control without CFHC
172EP		red-and-white warning stripes on doors and air deflectors
201HL		Air-intake half-height behind cab. With dry air filter/pre-separator
205AP		1-cyl. compressor 238 cc
206AR		exhaust upswept left
206TA		elbow for upswept or raised exhaust
208AB		engine brake with additional actuation via brake pedal
208XD		without exhaust valve brake (EVB)
210AA		flame starting system
211AD		clutch with 395 mm diameter
219AF		steering oil reservoir with dipstick
230AC		with underride guard at rear
230ER		front underride guard
230YX		without lateral underride guard
232HC		synthetic bumper
236CS		rear cross member for trailer coupling 160X100
241AE		body mounting brackets on frame
245XX		without spare wheel holder
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)
259CA		disc brake for front axle
259CB		disc brake for rear axle
262XX		without brake connection on frame end
278AE		Air filler connection at front
283FR		Cab mounts on coil springs for 'C' cab
303AX		Lockable tank fastener - 1 u. ventilated for master key system
309AA		Beam throw regulator
310EE		Halogen twin headlights H7 for right-hand traffic
318AA		marker lamps
318AK		lateral marker lights
319YX		without reading light
321EC		central locking
324AA		Single-tone horn, electric
325AA		MAN Tronic (on-board computer)
326FZ		Socket in cab 12V 2-pole and 24V 2-pole
326XY		Without 12/24 V socket on end of frame
327AF		battery main switch, mechanical
329CT		Two 12-V 175-Ah batteries
329ED		Battery box lockable (without lock)
329HC		Maintenance sign for batteries - 'maintenance-free'
33VAC		engine capsule
331CY		28V three-phase alternator 120A 3360W Longlife Eco
339FP		Display on the dashboard for operating data

343AZ		Warning buzzer in seven-chamber light when reverse gear engaged
345AU		Maximum electronic speed limitation 89 km/h
345EA		cruise control
348AA		Coolant level indicator in cab
350LK		CB radio antenna on cab roof
350NK		Radio MAN CD 24V
351AF		preparation for radiotelephone
352CF		2 halogen revolving beacons on cab roof left and right
352WS		Revolving beacon, yellow
362AA		Stabiliser for rear axle
363AA		Stabiliser for front axle
370CR		air dryer, heated
373AE		antifreeze effective down to -35 degrees
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL		No bunks for 'M' , 'C' , 'DK' cabs
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YA		Without all-roand curtain for C/M cab
384CD		Safety belt display, driver's side
386AS		Mechanical sliding roof
387AF		Electric door window lifters for driver and co-driver
388AB		Folding sunshade for driver and co-driver
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390AX		storage compartment above windscreen
390XB		without pigeon hole on rear wall
390XX		without oddment box
392AK		rear-view mirror(s) heatable and electrically adjustable
392AR		kerb mirror, right, heated and electrically adjustable
392AS		Wide-angle mirror, right, heatable and electrically adjustable
392AW		kerb mirror, left, heatable and electrically adjustable
392AX		wide-angle mirror, left, heated and electrically adjustable
392CL		EU front mirror on co-driver's side
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
394FM		1 Fire extinguisher, 2 kg, multilingual (English/German/Dutch)
396CC		windscreen washer electric
400AH		mudflap front
401AF		temporary transport mudguards
401CW		deletion of plastic mudguards
404AP		spray reducer
405AC		Bonding set, separate

405AK		hazard-warning sign
405AR		hazard-warning lamp
405CP		20 m tyre inflator hose with pressure gauge
407AN		Jack, 10 t
411AG		chock with bracket, loose
434ES		dashboard in standard version
524IB		Load variant 16000 kg
538AE		plastic floor and engine tunnel covering
542DM		Supplier declaration
542FC		anti-noise package 80 dB (92/97EEC)
542IZ		confirmation for international registration
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab DEEP ORANGE 2011
80001		2 wahlweise 295/80R22,5 LENK-S+G TL
90001		4 wahlweise 295/80R22,5 ANTR-S+G TL
90004		1 wahlweise 295/80R22,5 LENK-S+G TL

### Weights:

Gross weight: 16000

1st front axle: 7100

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 11500

2nd rear axle: 0

Trailing axle: 0