

## Model : TGM 18.240 4X2 BB

### Technical extent of delivery

| Code  | Customer Special Request | Designation                                                   |
|-------|--------------------------|---------------------------------------------------------------|
| 000AA |                          | Non-variable parts                                            |
| 001AC |                          | steering arrangement, right                                   |
| 005BJ |                          | Wheelbase 3575 mm                                             |
| 006EV |                          | rear frame overhang 1125 mm                                   |
| 018MK |                          | D0836LFL40 engine - 240 hp/176 kW EURO 3 - 925 Nm Common Rail |
| 02AAB |                          | instrument panel kmh 'Base-Line'                              |
| 022SF |                          | gearbox ZF 12 AS 1210 OD MAN TipMatic                         |
| 023FT |                          | fuel tank 150l right                                          |
| 025MU |                          | front axle VOK-07 dropped                                     |
| 026EA |                          | front springs parabolic 7.1 t                                 |
| 027AC |                          | radiator and intercooler                                      |
| 028EB |                          | rear springs parabolic, 11.5 t                                |
| 03KAA |                          | fuel tank fitted                                              |
| 030AC |                          | hydraulic steering                                            |
| 030EE |                          | steering wheel with height and inclination adjustment         |
| 032AB |                          | MAN BrakeMatic (electronic brake system)                      |
| 034NH |                          | hypoid rear axle HY-1133                                      |
| 035FE |                          | Hypoid axle ratio i = 5.29                                    |
| 037AC |                          | with differential lock in rear axle                           |
| 038GC |                          | disc wheels 10 hole 8.25-22.5 on 1stFA TL                     |
| 038PC |                          | disc wheels 10-hole 8.25-22.5 on 1stRA TL                     |
| 038TC |                          | disc wheel 10-hole 8.25-22.5 as spare wheel TL                |
| 042XY |                          | without electronic tachograph                                 |
| 050NK |                          | C cab 2240mm wide, 1620mm long                                |
| 052XA |                          | without stowage boxes                                         |
| 058BA |                          | seat coverings in standard quality                            |
| 058NH |                          | driver's seat, high-comfort, with air suspension              |
| 059HC |                          | Static co-driver's seat with storagebox                       |
| 064AC |                          | two additional vehicle keys                                   |
| 080AE |                          | door interior panelling washable                              |
| 116AE |                          | visco fan                                                     |
| 118MA |                          | EDC engine regulation                                         |
| 121EH |                          | neutral pos. switch                                           |
| 123CC |                          | strainer for fuel tank                                        |
| 123CE |                          | chain for tank cap                                            |
| 124AL |                          | fuel filter                                                   |
| 124AR |                          | additional fuel filter heated with water trap, make SEPAR     |
| 124EA |                          | fuel filter heating                                           |

|       |                                                                                  |
|-------|----------------------------------------------------------------------------------|
| 142AF | calibrate tachograph                                                             |
| 153KC | air conditioning system AC R134A with automatic temperature control without CFHC |
| 172EP | red-and-white warning stripes on doors and air deflectors                        |
| 201HL | Air-intake half-height behind cab. With dry air filter/pre-separator             |
| 205AP | 1-cyl. compressor 238 cc                                                         |
| 206AR | exhaust upswept left                                                             |
| 206TA | elbow for upswept or raised exhaust                                              |
| 208AB | engine brake with additional actuation via brake pedal                           |
| 208XD | without exhaust valve brake (EVB)                                                |
| 210AA | flame starting system                                                            |
| 211AD | clutch with 395 mm diameter                                                      |
| 219AF | steering oil reservoir with dipstick                                             |
| 230AC | with underride guard at rear                                                     |
| 230ER | front underride guard                                                            |
| 230YX | without lateral underride guard                                                  |
| 232HC | synthetic bumper                                                                 |
| 236CS | rear cross member for trailer coupling 160X100                                   |
| 241AE | body mounting brackets on frame                                                  |
| 245XX | without spare wheel holder                                                       |
| 256AA | steering wheel lock                                                              |
| 258HA | anti-lock braking system (ABS)                                                   |
| 259CA | disc brake for front axle                                                        |
| 259CB | disc brake for rear axle                                                         |
| 262XX | without brake connection on frame end                                            |
| 278AE | Air filler connection at front                                                   |
| 283FR | Cab mounts on coil springs for 'C' cab                                           |
| 303AX | Lockable tank fastener - 1 u. ventilated for master key system                   |
| 309AA | Beam throw regulator                                                             |
| 310EE | Halogen twin headlights H7 for right-hand traffic                                |
| 318AA | marker lamps                                                                     |
| 318AK | lateral marker lights                                                            |
| 319YX | without reading light                                                            |
| 321EC | central locking                                                                  |
| 324AA | Single-tone horn, electric                                                       |
| 325AA | MAN Tronic (on-board computer)                                                   |
| 326FZ | Socket in cab 12V 2-pole and 24V 2-pole                                          |
| 326XY | Without 12/24 V socket on end of frame                                           |
| 327AF | battery main switch, mechanical                                                  |
| 329CT | Two 12-V 175-Ah batteries                                                        |
| 329ED | Battery box lockable (without lock)                                              |
| 329HC | Maintenance sign for batteries - 'maintenance-free'                              |
| 33VAC | engine capsule                                                                   |
| 331CY | 28V three-phase alternator 120A 3360W Longlife Eco                               |
| 339FP | Display on the dashboard for operating data                                      |

|       |                                                                 |
|-------|-----------------------------------------------------------------|
| 343AZ | Warning buzzer in seven-chamber light when reverse gear engaged |
| 345AU | Maximum electronic speed limitation 89 km/h                     |
| 345EA | cruise control                                                  |
| 348AA | Coolant level indicator in cab                                  |
| 350LK | CB radio antenna on cab roof                                    |
| 350NK | Radio MAN CD 24V                                                |
| 351AF | preparation for radiotelephone                                  |
| 352CF | 2 halogen revolving beacons on cab roof left and right          |
| 352WS | Revolving beacon, yellow                                        |
| 362AA | Stabiliser for rear axle                                        |
| 363AA | Stabiliser for front axle                                       |
| 370CR | air dryer, heated                                               |
| 373AE | antifreeze effective down to -35 degrees                        |
| 376XH | Without Mattress for lower bunk                                 |
| 376XK | Without Mattress for upper bunk                                 |
| 376XL | No bunks for 'M' , 'C' , 'DK' cabs                              |
| 380AC | windscreen of laminated glass tinted                            |
| 380CA | door windows tinted                                             |
| 381AA | cab rear wall without windows                                   |
| 381XC | Without curtain before bunks                                    |
| 381YA | Without all-roand curtain for C/M cab                           |
| 384CD | Safety belt display, driver's side                              |
| 386AS | Mechanical sliding roof                                         |
| 387AF | Electric door window lifters for driver and co-driver           |
| 388AB | Folding sunshade for driver and co-driver                       |
| 389AC | handles left and right (on B-post)                              |
| 389AD | handles left and right (on A-post)                              |
| 390AX | storage compartment above windscreen                            |
| 390XB | without pigeon hole on rear wall                                |
| 390XX | without oddment box                                             |
| 392AK | rear-view mirror(s) heatable and electrically adjustable        |
| 392AR | kerb mirror, right, heated and electrically adjustable          |
| 392AS | Wide-angle mirror, right, heatable and electrically adjustable  |
| 392AW | kerb mirror, left, heatable and electrically adjustable         |
| 392AX | wide-angle mirror, left, heated and electrically adjustable     |
| 392CL | EU front mirror on co-driver's side                             |
| 392HA | Mirror brackets for body width 2500-2600 mm width 2500 mm       |
| 394FM | 1 Fire extinguisher, 2 kg, multilingual (English/German/Dutch)  |
| 396CC | windscreen washer electric                                      |
| 400AH | mudflap front                                                   |
| 401AF | temporary transport mudguards                                   |
| 401CW | deletion of plastic mudguards                                   |
| 404AP | spray reducer                                                   |
| 405AC | Bonding set, separate                                           |

|       |                                             |
|-------|---------------------------------------------|
| 405AK | hazard-warning sign                         |
| 405AR | hazard-warning lamp                         |
| 405CP | 20 m tyre inflator hose with pressure gauge |
| 407AN | Jack, 10 t                                  |
| 411AG | chock with bracket, loose                   |
| 434ES | dashboard in standard version               |
| 524IB | Load variant 16000 kg                       |
| 538AE | plastic floor and engine tunnel covering    |
| 542DM | Supplier declaration                        |
| 542FC | anti-noise package 80 dB (92/97EEC)         |
| 542IZ | confirmation for international registration |
| 542NC | Registration as N3 vehicle, (GVW > 12t)     |
| 600AC | Fittings for right-hand traffic             |
| LQW01 | chassis in water-based paint                |
| LVS01 | chassis graphite black RAL 9011 matt        |
| LVS02 | wheels White aluminium acrylic RAL 9006     |
| LVS03 | cab DEEP ORANGE 2011                        |
| 80001 | 2 wahlweise 295/80R22,5 LENK-S+G TL         |
| 90001 | 4 wahlweise 295/80R22,5 ANTR-S+G TL         |
| 90004 | 1 wahlweise 295/80R22,5 LENK-S+G TL         |

**Weights:**

Gross weight: 16000  
 1st front axle: 7100  
 2nd front axle: 0  
 3rd front axle: 0  
 Leading axle: 0  
 1st rear axle: 11500  
 2nd rear axle: 0  
 Trailing axle: 0