

## Model : TGS 41.400 8X4 BB-WW

<b>Sales centre/country:</b>	Togo sonstige
<b>Place of production:</b>	MÜNCHEN
<b>Vehicle model:</b>	TGS 41.400 8X4 BB-WW
<b>Basic vehicle</b>	L 39W AE 01

### Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005UH		Wheelbase 1795+2505+1400 mm
006CI		rear frame overhang 800 mm
018SI		engine D2066LF06 - 400 hp / 294 KW EURO2 - 1900 Nm Common-Rail
02AAG		Instrument panel km/h 'High-Line in colour'
022H3		Gearbox ZF 16 S 223 OD
023CT		fuel tank 300l right
025ML		front axle VO-09/VO-09 straight
026EF		front springs parabolic 9,5 t
027AP		radiator and intercooler for over 35degrees ambient temperature
028EC		rear springs parabolic 13 t
028PA		Fit tandem axles
029GC		Propshafts for high load profile
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034MH		hub-reduction rear axle HPD-1382/ HP-1352
035KL		Planetary axle ratio i = 4.00
037AC		with differential lock in rear axle
038GG		disc wheels 10 hole 9.00-22.5 on 1stFA TL
038JG		disc wheels 10-hole 9.00-22.5 on 2ndfront axle TL
038PG		disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG		disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038TG		disc wheel 10-hole 9.00-22.5 as spare wheel TL
042XY		without electronic tachograph
05NAE		front panel unlockable from inside
050NN		M cab 2240mm wide, 1880mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality
058NH		driver's seat, high-comfort, with air suspension
059NA		co-driver's seat static, with longitudinal + seat back adjustment

080AE	door interior panelling washable
116AE	visco fan
118EK	Short mounting base (engine only)
118MA	EDC engine regulation
119EH	General PTO parameterisation
122QN	PTO NH/4C without flange f=1.17/1.40right horizontal
123CC	strainer for fuel tank
124AL	fuel filter
124AZ	Auxiliary fuel filter with water separator
133MA	actuating system for tipper body
150WR	Brushed aluminium insert on instrument panel
153KA	air conditioning system AC R134A without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194AB	operator's manual in English
201AS	air intake raised with dry air filter
201EM	Air filter cartridge with safety insert for heavy-duty deployment
201FA	fine dust and pollen filter
203EK	connection for external engine speedcontrol (ZDR)
205AN	air compressor 1-cylinder, 360 ccm
206EY	exhaust on rh side with tail pipe to rear
208XD	without exhaust valve brake (EVB)
210XX	Without flame-start/jump-start system
211FQ	Single-disc clutch DTE 430, reinforced
227AC	rear axle breather upswept
230AH	rear underride guard, round
230XW	Without front underride guard
230YX	without lateral underride guard
233EM	3-part steel bumper
236AF	cross member for trailer coupling
241AC	without platform mounting brackets
245XX	without spare wheel holder
256AA	steering wheel lock
256EA	emergency steering pump
258HA	anti-lock braking system (ABS)
259CA	disc brake for front axle
259CE	drum brake for rear axle
262XX	without brake connection on frame end
272FA	Entry lighting for driver and co-driver
280AC	wiring for tank truck to ADR
280EC	Fly mesh guard before radiator
281AB	medium-height design
283FB	Cab mounts on coil springs for 'M' cab
303AT	Non-lockable tank cap 1 u. non-ventilated (not eligible for approval/registration according to ECE-R34)
310EE	Halogen twin headlights H7 for right-hand traffic
318AA	marker lamps
318AK	lateral marker lights

319AR		reading lamp for driver
321EC		central locking
324AC		Two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EC		Language 1 'English' for display in instrument panel
325FE		Language 2 'French' for display in instrument panel
326XY		Without 12/24 V socket on end of frame
327AF		battery main switch, mechanical
329AS		Batteries 12 V 150 Ah, 2 units
329ER		Battery box up to 175 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331AB		Basic alternator
339FP		Display on the dashboard for operating data
345CV		Maximum electronic speed limitation 85 km/h
345EA		cruise control
346CA		charging pressure indicator
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350XO		Without navigation SD
351US		AUX-IN/USB in the instrument panel
352DX		2 LED revolving beacons on cab roof,left and right
352WS		Revolving beacon, yellow
358AA		ETA electric cutout
362AH		Stabiliser on both rear axles
363AA		Stabiliser for front axle
370CM		air dryer
373AE		antifreeze effective down to -35 degrees
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL		No bunks for 'M' , 'C', 'DK' cabs
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-roand curtain
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386XA		Without lifting roof
387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
388AK		sun shade in front of windscreen
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390CT		cup holder in dashboard
390XX		without oddment box
392AH		kerb mirror, right
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm

392XJ		Without front mirror on co-driver's side/at centre
400AH		mudflap front
401CW		deletion of plastic mudguards
401EL		3-part synthetic mudguards for 2nd front axle
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
407XX		Without jack
411AA		1 chock
434DA		Interior design in Sand
44VCA		Crankcase ventilation closed
523AC		signs in English
538AE		plastic floor and engine tunnel covering
542FX		anti-noise measures are not in accordance with EU standard
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
798LF		Height over cab, unloaded up to 4000mm
798WF		vehicle cannot be registered to directive 2000/40/EC. Exceptions possible under cert. circumstances.
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Pure white RAL 9010
80001		2 wahlweise 315/80R22,5 LENK-S+G TL
80002		2 wahlweise 315/80R22,5 LENK-S+G TL
90001		4 wahlweise 315/80R22,5 ANTR-S+G TL
90002		4 wahlweise 315/80R22,5 ANTR-S+G TL
90004		1 wahlweise 315/80R22,5 LENK-S+G TL

**Weights:**

Gross weight: 41000  
 1st front axle: 8000  
 2nd front axle: 8000  
 3rd front axle: 0  
 Leading axle: 0  
 1st rear axle: 13000  
 2nd rear axle: 13000  
 Trailing axle: 0