

Model : TGM 18.280 4X4 BB

Place of production:	STEYR
Vehicle model:	TGM 18.280 4X4 BB
Basic vehicle	L N64 EH 31

Technical extent of delivery

Code	Customer Special Request	Designation
001AC		steering arrangement, right
005CU		wheelbase 4500 mm
006OB		rear frame overhang 2325 mm
018NL		engine D0836LFL41 - 280 hp / 206 kw EURO3 - 1100 Nm Common Rail
02AAB		instrument panel kmh 'Base-Line'
021GG		Gearbox software MAN TipMatic Offroad (off-road deployment)
022SF		MAN TipMatic 12 12 OD gearbox
023GM		Fuel tank 300l right
025MS		front axle VP-09 driven
026EA		front springs parabolic 7.1 t
027AC		radiator and intercooler
028CY		parabolic rear springs, 9 t
03KAA		fuel tank fitted
030AC		hydraulic steering
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EA		brake shoe width 180 mm for rear axle
034MF		hub-reduction rear axle HP-1333 single tyred
035KM		Planetary axle ratio $i = 5.33$
037AC		with differential lock in rear axle
038EW		disc wheels 10-hole 10.00-20 on 1st FA TL
038FQ		disc wheel 10-hole 10.00-20 as sparewheel TL
038FX		disc wheels 10-hole 10.00-20 on 1st RA TL for single tyres
042XY		without electronic tachograph
050NF		L cab 2240mm wide, 2280mm long
052AC		Storage box accessible from inside and outside - flap unlocked from inside
057EX		Type symbols (supplied loose)
058BA		seat coverings in standard quality
058NA		driver's seat static, longitudinal adjustment and seat back adjustment
059NA		co-driver's seat static, with longitudinal + seat back adjustment
080AE		door interior panelling washable
116AE		visco fan
118AP		Engine number also on crankcase
118MA		EDC engine regulation

120EK		deep oil pan for gradeability up to 60%, oil quantity 16/20L
121EH		neutral pos. switch
123CC		strainer for fuel tank
123CE		chain for tank cap
124AL		fuel filter
124AM		additional fuel filter with water trap, make SEPAR
124EA		fuel filter heating
142AF		calibrate tachograph
146AB		transfer case G 102
146AF		front wheel drive (dis)engageable
146CD		Transfer box management (VSM)
150KZ		BW equipment type H&K G36 for cab (2brackets)
153KC		air conditioning system AC R134A with automatic temperature control without CFHC
194AB		operator's manual in English
201CR		air intake upswept with dry air filter behind cab / precleaner
205AP		1-cyl. compressor 238 cc
206ED		Exhaust right with tailpipe angled right
208AB		engine brake with additional actuation via brake pedal
208XD		without exhaust valve brake (EVB)
210XX		Without flame-start/jump-start system
211AD		clutch with 395 mm diameter
219AF		steering oil reservoir with dipstick
227AU		fordability up to 700 mm
227EA		transfer case breather raised
230AC		with underride guard at rear
230YX		without lateral underride guard
233EK		steel bumper
234AX		towing coupling ROCKINGER SK5
236CS		rear cross member for trailer coupling 160X100
241AC		without platform mounting brackets
245XX		without spare wheel holder
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)
259CC		drum brake for front axle
259CE		drum brake for rear axle
262AL		2-line brake connection at end of frame
272FA		Entry lighting for driver and co-driver
278AE		Air filler connection at front
281AA		high design
283FN		Cab mounts air suspended at rear
303AX		Lockable tank fastener - 1 u. ventilated for master key system
309AA		Beam throw regulator
310EK		Halogen headlights H1 for left-hand traffic
310LA		blackout lighting

310PX		Wiring harness 1m for 7-pole trailersocket at frame end, supplied loose
318AA		marker lamps
318YX		Without lateral marker lights
319AA		reading lamps for driver and co-driver
321XE		Without central locking
322AL		Lights front axles
322CM		3-chamber taillight
324AA		Single-tone horn, electric
325AA		MAN Tronic (on-board computer)
325EC		Language 1 'English' for display in instrument panel
326CK		trailer socket for anti-skid system on frame end
326CW		7+7-pin 24 V trailer socket at end of frame
327AF		battery main switch, mechanical
329ED		Battery box lockable (without lock)
329HC		Maintenance sign for batteries - 'maintenance-free'
329XG		without batteries 2x88 Ah
33VAC		engine capsule
331AB		Basic alternator
333AL		starter watertight
339FP		Display on the dashboard for operating data
345AU		Maximum electronic speed limitation 89 km/h
345EA		cruise control
348AA		Coolant level indicator in cab
350NK		Radio MAN CD 24V
352FD		Preparation for installation of flashing beacons
362AA		Stabiliser for rear axle
363AA		Stabiliser for front axle
370CM		air dryer
376FA		1 bunk with storage space (with aluminium frame).
376HA		Mattress for lower bunk
376KA		Bunk cover for bottom bunk
376XK		Without Mattress for upper bunk
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381CE		All-roand curtain
381XC		Without curtain before bunks
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386AS		Mechanical lifting roof
387AG		Mechanical door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
389AB		Grab handles on left and right (on B-pillar) with mounting points for subsequent attachments

389AD		handles left and right (on A-post)
390AX		storage compartment above windscreen
390XB		without pigeon hole on rear wall
390XX		without oddment box
392AG		Kerb mirror, left
392AL		mechanical wide-angle mirror, right
392AT		mech. wide-angle mirror, left
392AY		rear view mirror, mech. adjustable
392CL		EU front mirror on co-driver's side
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
395AA		ashtray on co-driver's side
396CC		windscreen washer electric
400XX		front mudflaps deleted
401CW		deletion of plastic mudguards
404XG		without spray reduction facility
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
405CP		20 m tyre inflator hose with pressure gauge
407XX		Without jack
411AA		1 chock
434AF		cigar lighter and socket
434ES		dashboard in standard version
538AF		carpeted engine tunnel
542FX		anti-noise measures are not in accordance with EU standard
600AA		Fittings for left-hand traffic
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Pure white RAL 9010
80001		2 (395/85R20)
90001		2 (395/85R20)
90004		1 (395/85R20)

Weights:

Gross weight: 16000
 1st front axle: 7100
 2nd front axle: 0
 3rd front axle: 0
 Leading axle: 0
 1st rear axle: 9000
 2nd rear axle: 0