



Vehicle description for: TGS 26.320 6x2-4 BL CH



Illustration can deviate

Vehicle standards		
	Product family	The new MAN Truck Generation
	Model & Variant	TGS 26.320 6x2-4 BL CH
	Vehicle type	Vehicle type, platform truck and chassis (LK)
	Cab	Local transport cab NN
	Main wheel distance	3600 mm
	Overhang	1550 mm
	Steering configuration	Left

Vertical Load		
	National Registration	Technical Load
Gross weight	25,000 kg	26,000 kg
Front axle	8,000 kg	8,000 kg
Rear axle	10,000 kg	10,000 kg
Trailing axle	9,000 kg	9,000 kg

Horizontal Load		
	National Registration	Technical Load
Gross train weight	0 kg	0 kg



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, heavy	0P2UC
<input type="checkbox"/>	Destination: Russian Federation (RU)	0P3I5
<input type="checkbox"/>	Merchant tonnage 26 t	0P8LH
<input type="checkbox"/>	Basic layout of vehicle, all-round	0PGCU
<input type="checkbox"/>	Frame type, normal height	0P2TS
<input type="checkbox"/>	Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documentation in Russian	0P2LP
<input type="checkbox"/>	Labelling in Russian	0P8NR
<input type="checkbox"/>	Cab position 640 mm (distance from frame lower edge to cab floor)	0PHBE

Registration

<input type="checkbox"/>	Vehicle approval, N3 class	0P3JR
<input type="checkbox"/>	Maximum speed limiter, 89 km/h, tolerance +1 km/h, electronic, engine speed regulation	0P2UJ
<input type="checkbox"/>	Maximum vehicle noise level, 80 dB in acc. with UN/ECE-R 51.02	0PINC
<input type="checkbox"/>	Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/>	Data confirmation for issue of German export registration number	0P2U6
<input type="checkbox"/>	Without registration documentation, national	0P3B0
<input type="checkbox"/>	Special confirmation, heavy load / municipal operation	0P3CK

Application scope / transport tasks

<input type="checkbox"/>	Disposal	0P6WP
<input type="checkbox"/>	Increase of the tyre load capacity by 10% (for communal supplement)	0P0UU
<input type="checkbox"/>	202 Refuse collector, rear loader	0P2RM
<input type="checkbox"/>	Temperate range, vehicle deployment, moderate	0P0G7
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Special request paintwork	0PJTD
--------------------------	---------------------------	-------

Horizontal and vertical loads

<input type="checkbox"/>	25,000 kg permitted gross load, vertical, nat. appr.	0P5PY
<input type="checkbox"/>	26,000 kg permitted gross load, vertical, tech.	0P5TV
<input type="checkbox"/>	26,000 kg permitted gross load, vertical, tech. Plus	0P8HJ
<input type="checkbox"/>	8,000 kg permitted load on front axle, nat. appr.	0P5KT
<input type="checkbox"/>	8,000 kg permitted load on front axle, tech.	0P5LN
<input type="checkbox"/>	8,000 kg permitted load on front axle, tech. Plus	0P8D4
<input type="checkbox"/>	10,000 kg permitted load on rear axle NatZu	0P5GW
<input type="checkbox"/>	10,000 kg permitted load on rear axle, tech.	0P5H8
<input type="checkbox"/>	10,000 kg permitted load on rear axle, tech. Plus	0P8A9



<input type="checkbox"/>	9,000 kg permitted load on trailing axle, nat. appr.	0P5JC
<input type="checkbox"/>	9,000 kg permitted load on trailing axle, tech.	0P5JX
<input type="checkbox"/>	9,000 kg permitted load on trailing axle, tech. Plus	0P8CS
<input type="checkbox"/>	0kN D value	0P8XD

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/>	Main wheelbase, 3,600 mm	0P2ZD
<input type="checkbox"/>	Wheelbase between rear axle and trailing axle, 1,350 mm	0P3BR
<input type="checkbox"/>	Frame overhang, rear, 1,550 mm	0P3D7
<input type="checkbox"/>	Main frame side member thickness, 8 mm	0P0Y6
<input type="checkbox"/>	Vehicle rear, straight end of frame	0P0XT

Exhaust system, air intake

<input type="checkbox"/>	Exhaust silencer, side, left	0P1BG
<input type="checkbox"/>	Exhaust tailpipe, towards rear	0P1BQ
<input type="checkbox"/>	Air intake, behind cab, raised	0P0AY

Battery cases, batteries, alternator

<input type="checkbox"/>	Battery, 12 V, 230 Ah, 2 units, maintenance free	0P4I1
<input type="checkbox"/>	Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco	0P1BW
<input type="checkbox"/>	Large battery box, 2 batteries	0P0WR
<input type="checkbox"/>	Battery box, left	0P0WO
<input type="checkbox"/>	Main battery switch, mechanical	0P0WF
<input type="checkbox"/>	Fuses	0P1V1

Tanks and fuel line

<input type="checkbox"/>	Guard plate for tanks	0P1DL
<input type="checkbox"/>	Fuel tank capacity 400 l, right	0P4ED
<input type="checkbox"/>	Fuel tank, right, steel	0P4GN
<input type="checkbox"/>	Tank cross-section, right, medium	0P4HE
<input type="checkbox"/>	AdBlue tank capacity 35 l, right	0P4CZ
<input type="checkbox"/>	AdBlue tank, right, plastic	0P4HU
<input type="checkbox"/>	Fuel tank cap, lockable for master key system	0P4H5
<input type="checkbox"/>	Cap for AdBlue tank, lockable	0P4GE
<input type="checkbox"/>	Filter screen for fuel tank filler neck	0P1EM

Frame attachments

<input type="checkbox"/>	Underride protection, front	0P1FN
<input type="checkbox"/>	Without working platform	0P0VH
<input type="checkbox"/>	Underride protection, side	0P1FH
<input type="checkbox"/>	Spare wheel hoist on left side, in front of rear axle	0P0XO
<input type="checkbox"/>	Hoist for spare wheel	0P0VN
<input type="checkbox"/>	Final cross member, with hole pattern 160 x 100 mm	0P1SB
<input type="checkbox"/>	Without underride protection, rear	0P1FB
<input type="checkbox"/>	Wheel chock, 2 unit, with retaining device	0P1FQ
<input type="checkbox"/>	Body attachment bracket	0P0X5



Pneumatic brakes, compressed-air generation, brake system

<input type="checkbox"/>	Air compressor, 1-cylinder, 360 ccm	0P0AF
<input type="checkbox"/>	Air dryer, heated	0P0B2
<input type="checkbox"/>	Compressed-air treatment, pneumatically controlled	0P0AB
<input type="checkbox"/>	Steel compressed-air tank	0P0XH
<input type="checkbox"/>	Electronic brake system (EBS)	0P0BL
<input type="checkbox"/>	Anti-lock braking system (ABS)	0P0BE
<input type="checkbox"/>	Full brake assistant	0P0CM
<input type="checkbox"/>	MAN EVBec high-performance engine brake, stages possible	0P0BW
<input type="checkbox"/>	Disc brakes on front axle	0P1I9
<input type="checkbox"/>	Disc brakes on rear axle	0P1I4
<input type="checkbox"/>	Disc brakes on trailing axle	0P1I8
<input type="checkbox"/>	Parking brake control, next to driver's seat	0P3KH
<input type="checkbox"/>	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/>	Parking brake, on front axle(s), pneumatic, additional, exhaustible	0P0C1
<input type="checkbox"/>	MAN EasyStart immobiliser	0P1TF
<input type="checkbox"/>	Brake lining thickness display, with brake lining wear warning	0P0BG
<input type="checkbox"/>	Harmonisation of brake lining wear	0P0BI

Lights and acoustic signals on the chassis (rear lights, ...)

<input type="checkbox"/>	Rear lights	0P2AQ
<input type="checkbox"/>	Acoust. Reversing warning system when reverse gear selected	0P3CD
<input type="checkbox"/>	Light function test	0P2AD
<input type="checkbox"/>	Side marker lights, LED	0P2BJ

Driveline/running gear

Engine, radiator

<input type="checkbox"/>	Diesel engine MAN D2066 LF43, 235 kW (320 hp) output, 1,600 Nm torque, Euro 5	0P6BF
<input type="checkbox"/>	Fuel filter, heated, for fuels up to Cleanliness Class 21	0PHIF
<input type="checkbox"/>	Fuel pre-filter, with oil separator/water trap, heated	0P0AU
<input type="checkbox"/>	Ventilation, crankcase, closed	0P8PM
<input type="checkbox"/>	Anti-noise skirt, engine	0P2E7
<input type="checkbox"/>	Engine cooler, normal length	0P4XX
<input type="checkbox"/>	Front radiator protection, grille	0P1VP
<input type="checkbox"/>	Engine oil dipstick and digital oil level gauge	0P0B6
<input type="checkbox"/>	Warning message for engine coolant level, with advance warning	0P0KA
<input type="checkbox"/>	Antifreeze, down to -32 °C	0P0AK
<input type="checkbox"/>	Engine protection function in idle mode, very low temperatures	0P0IZ
<input type="checkbox"/>	Flame-start system	0P0GD
<input type="checkbox"/>	Cover for intercooler	0P1X4
<input type="checkbox"/>	Engine number, additionally on crankshaft housing	0P0IV

Gearbox, clutch

<input type="checkbox"/>	MAN TipMatic 12.26 DD	0P5VS
<input type="checkbox"/>	Gearbox for increased percentage of overrun during driving operation	0PGCL
<input type="checkbox"/>	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI



<input type="checkbox"/>	MAN Idle Speed Driving gearbox function	0P0ER
<input type="checkbox"/>	Rock-free gearbox function	0P0EV
<input type="checkbox"/>	MAN TipMatic Efficiency driving program, up to 70,000 kg	0P0FA
<input type="checkbox"/>	Single-disc clutch, 430 mm, dry, reinforced (LongLife)	0P0DW

Wheels, tyres

<input type="checkbox"/>	Required tyre speed index K	0PFW3
<input type="checkbox"/>	Front axle tyres optionally 385/65R22.5 Steering-Long-haul TL (160 K)	0PEWI
<input type="checkbox"/>	Rim type, front axle, steel, single-part	0P0P0
<input type="checkbox"/>	Rim size, front axle, 10-hole, 11.75x22.5	0P0NB
<input type="checkbox"/>	Wheel nut cover ring, front axle	0P0PR
<input type="checkbox"/>	Rear axle tyres optionally 315/80R22.5 Drive-Short-haul TL (154/150 K)	0PDRW
<input type="checkbox"/>	Rim type, rear axle, steel, single-part	0P0OO
<input type="checkbox"/>	Rim size, rear axle, 10-hole, 9.00x22.5	0P0MU
<input type="checkbox"/>	Trailing axle tyres optionally 385/65R22.5 Steering-Long-haul TL (160 K)	0PEKB
<input type="checkbox"/>	Rim type, trailing axle, steel, single-part	0P0OT
<input type="checkbox"/>	Rim size, trailing axle, 10-hole, 11.75x22.5	0P0N4
<input type="checkbox"/>	Wheel nut cover ring, trailing axle	0P0PN
<input type="checkbox"/>	Spare wheel, in accordance with configuration for front axle tyres	0P0MH
<input type="checkbox"/>	Tyre inflation hose, 20 m, with pressure gauge	0P1UA

Axles

<input type="checkbox"/>	6x2-4	0P3B8
<input type="checkbox"/>	Steering ratio, indirect	0P1JY
<input type="checkbox"/>	Steering oil tank with electrical measuring sensor	0P1JV
<input type="checkbox"/>	Front axle, 9,200 kg, not driven, cranked, steered, not liftable	0P5EV
<input type="checkbox"/>	Mudguard, front axle	0P1AT
<input type="checkbox"/>	Splash guard mat on mudguard, front axle, longer at bottom	0P1XS
<input type="checkbox"/>	Rear axle, 13,000 kg, HY axle without drive shaft, straight, not steered, not liftable	0P4ZP
<input type="checkbox"/>	Twin tyre on rear axle	0P1HN
<input type="checkbox"/>	Mudguard, rear axle, upper shell removable	0P1AM
<input type="checkbox"/>	Splash guard mat on mudguard, rear axle, longer at bottom	0P1XK
<input type="checkbox"/>	Trailing axle, 9,000 kg, not driven, straight, steered, liftable	0P4Z1
<input type="checkbox"/>	Single tyre on trailing axle	0P1HP
<input type="checkbox"/>	Mudguard, trailing axle with removable upper shell	0P1AR
<input type="checkbox"/>	Splash guard mat on mudguard, trailing axle, longer at bottom	0P1XO
<input type="checkbox"/>	Axle ratio, $i = 3.36$	0P0CX
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Without differential locks, front axles	0P0DL
<input type="checkbox"/>	Oil for driven axles, high performance, fully synthetic	0P0DO
<input type="checkbox"/>	Digital axle load display (ALM) for air-sprung axles, cab	0P2IZ
<input type="checkbox"/>	Mudguard enlargement	0P1W5

Axle control system and suspension

<input type="checkbox"/>	Suspension type for front axles and driven rear axles, leaf/air (BL)	0P2YC
<input type="checkbox"/>	Control unit for electronically controlled air suspension (VASC)	0P3K9
<input type="checkbox"/>	Leaf-spring suspension on front axle, parabolic, 2-leaf, steel	0P1JD
<input type="checkbox"/>	Air suspension on rear axle, for high centre of gravity	0P1J6
<input type="checkbox"/>	Air suspension on trailing axle	0P1J8



<input type="checkbox"/>	Spring load-bearing capacity front axle 8,000 kg	0P5C2
<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 13,000 kg	0P5BV
<input type="checkbox"/>	Spring load-bearing capacity of trailing axle, 9,000 kg	0P5CE
<input type="checkbox"/>	Trailing axle relievable, moving-off aid with maximum speed limitation	0P1IM
<input type="checkbox"/>	Shock absorbers on front axle, reinforced	0P1M6
<input type="checkbox"/>	Shock absorbers on rear axle for high centre of gravity	0P1LR
<input type="checkbox"/>	Shock absorbers on trailing axle	0P1LV
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Stabiliser, trailing axle	0P1LL
<input type="checkbox"/>	Wishbone	0P6ZR

Cab

Cab and cab exterior

<input type="checkbox"/>	Local transport cab NN	0P2DL
<input type="checkbox"/>	Cab mount, Basic	0P1V8
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/>	No tilting roof/sliding roof	0P1VY
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	No sunblind, in front of windscreen	0P1WJ
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, rigid	0P1UZ
<input type="checkbox"/>	Central locking, no remote control	0P1WS
<input type="checkbox"/>	Vehicle key, 2 units	0P3JT
<input type="checkbox"/>	No door extension	0P1WW
<input type="checkbox"/>	Door labelling, according to trade tonnage of vehicle	0P2DQ
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Daytime driving lights, LED	0P2BP
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, bulb, 2 units	0P2BT
<input type="checkbox"/>	Comfort indicator function, can be activated	0P1ZW
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Preparation for loading area lighting	0P2A5

Mirrors and mirror replacements

<input type="checkbox"/>	Exterior rear-view mirror, electrically adjustable	0P2CA
--------------------------	--	-------



<input type="checkbox"/>	Mirror housing, not painted	0P2CP
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT
<input type="checkbox"/>	Kerb mirror, right, electrically adjustable	0P2CG
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ

Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Comfort driver's seat, air-sprung	0P2P2
<input type="checkbox"/>	Driver's seat arm rests	0P2OE
<input type="checkbox"/>	Adjustment of seat belt height, driver's seat	0P4XQ
<input type="checkbox"/>	Co-driver's seat, not sprung, length and backrest adjustment	0P2OQ
<input type="checkbox"/>	Middle seat, folding backrest, 2-point seatbelt	0P2PG
<input type="checkbox"/>	Indicator, seat belt, 1st row of seats, acoustic and visual	0P8L1

Driver's workplace

<input type="checkbox"/>	Multi-function steering wheel, adjustable height and angle	0P2GD
<input type="checkbox"/>	Steering wheel, with parking position	0P2GE
<input type="checkbox"/>	Steering lock	0P3JZ
<input type="checkbox"/>	Instrumentation, Basic km/h	0P3L3
<input type="checkbox"/>	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY
<input type="checkbox"/>	Tachograph, calibrated	0P2KG
<input type="checkbox"/>	Socket, cab centre, 2 units, 12 V and 24 V	0P2HX
<input type="checkbox"/>	Cigarette lighter	0P2IH
<input type="checkbox"/>	Preparation for radio with CB radio antenna on cab roof	0P2NK
<input type="checkbox"/>	Single DIN slots, 4 units, roof space, front	0P2FJ

Cab air-conditioning system

<input type="checkbox"/>	Air-conditioning system, manual	0P2NU
--------------------------	---------------------------------	-------

Bunk area

<input type="checkbox"/>	Without bunk area package	0PKNE
--------------------------	---------------------------	-------

Cab interior

<input type="checkbox"/>	Without interior lighting package	0PKNF
<input type="checkbox"/>	Colour scheme for interior styling, dark	0P2I6
<input type="checkbox"/>	Interior styling analogous to colour scheme	0PGBT
<input type="checkbox"/>	Windscreen roller blind, internal	0P2FE
<input type="checkbox"/>	Roller blind for door windows, internal, mechanical, driver's side	0P2FH
<input type="checkbox"/>	Interior light, central	0PHA6
<input type="checkbox"/>	Reading light, 1 unit, driver's side	0P2IQ
<input type="checkbox"/>	Entry lighting	0P2IO
<input type="checkbox"/>	Door interior cladding, washable	0P2IA
<input type="checkbox"/>	Storage, instrument panel in middle section, open	0P2HK
<input type="checkbox"/>	2 storage compartments, cab rear wall, behind driver's and co-driver's side and net on cab rear wall	0PGB8
<input type="checkbox"/>	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2
<input type="checkbox"/>	Entry handles, standard	0PHPK

Accessories and tools

<input type="checkbox"/>	Fire extinguisher, 2 kg, 1 ea., rear area of cab, inside, in vehicle documentation language	0P2YE
--------------------------	---	-------



<input type="checkbox"/>	Jack, 25,000 kg	0P3F9
<input type="checkbox"/>	Vehicle toolkit	0P2TX
<input type="checkbox"/>	Warning triangle, 1 units	0P3FI
<input type="checkbox"/>	Window cleaning set	0P3CI
<input type="checkbox"/>	Hazard warning light, 1 units, with continuous light function	0P3FF

Intelligent Truck

Assistance systems

<input type="checkbox"/>	Electronic Stability Program (ESP)	0P1TN
<input type="checkbox"/>	Anti-slip control (ASR)	0P1T2
<input type="checkbox"/>	Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/>	Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3
<input type="checkbox"/>	Without advanced emergency braking system	0P1U5

Infotainment (radio,...)

<input type="checkbox"/>	MMT infotainment system, Starter High	0P2M2
<input type="checkbox"/>	MAN loudspeaker system	0P2MF
<input type="checkbox"/>	No navigation map	0P2N2
<input type="checkbox"/>	Emergency call system eCall, manual	0P1TI

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/>	No fifth-wheel coupling	0P1RJ

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

<input type="checkbox"/>	Without trailer/towing coupling on final cross member	0P1NQ
<input type="checkbox"/>	Without trailer brake connection at end of frame, centre	0P1O0
<input type="checkbox"/>	Without trailer socket at frame end	0P1OW
<input type="checkbox"/>	Without trailer socket for anti-lock brake system (ABS)	0P1O9

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/>	Interface for data exch. with body (customer-specific control module) and engine intermediate speed control (ZDR), front area of cab	0P2NA
<input type="checkbox"/>	Interface for vehicle data (FMS)	0P2J3

PTOs

<input type="checkbox"/>	PTO, engine-dependent, non-shiftable	0P4N8
<input type="checkbox"/>	PTO, engine-dependent, flywheel, flange (6-hole, 100 mm), f=1.233, 650/720 Nm continuous/short	0P4W3
<input type="checkbox"/>	Flange connection on PTO, engine-dependent, 100 mm diameter (6-hole)	0P4OR
<input type="checkbox"/>	Engine-dependent power take-off, continuous operation	0P4XF
<input type="checkbox"/>	Double flange coupling for PTO, engine-dependent, elastic, supplied loose	0P4O8
<input type="checkbox"/>	Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/>	Sector-specific parameterisation, general	0P4X0

Towing, recovery and lashing



- ☐
- Central coupling jaw, integrated in bumper/front cross member, with lock pin
- 0P1MK

Paintworks

Paintwork, cab, top

- ☐
- Top coating, cab
- 0P6YB

Paintwork, cab, bottom

- ☐
- Textured coating, step units
- 0P6X9
- ☐
- Textured coating, mudguard, behind cab
- 0P6YG
- ☐
- Textured coating, bumper, steel
- 0P6YQ

Paintwork, chassis

- ☐
- Top coating, chassis
- 0P6YC
- ☐
- Top coating, rims, steel, white-aluminium
- 0P6YL

Colour

- ☐
- Top coating, cab
- PURE WHITE RAL 9010
- N
- ☐
- Top coating, chassis
- GRAPHITE BLACK RAL 9011
- W

df5a987c4-1c1b-4a17-9131-819ecd54494f



Technical data: TGS 26.320 6x2-4 BL CH / L19FAA01

Vehicle type: Vehicle type, platform truck and chassis (LK)

Cab: Local transport cab NN

Drive Type: 6x2-4

Lengths		mm
TD071	Total length	8107.0
TD063	Front vehicle overhang	1607.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	0
TD060	Wheelbase between rear axle and trailing axle	1350
TD064	Rear frame overhang	1550.0
TD072	Distance from first front axle to body	465.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	-

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

Frame		mm
TD009	Frame width at front	942.0
TD010	Frame width at the rear	762.0
TD078	Frame profile	270 x 85 x 8

Heights		mm
TD033	Maximum external height, unladen	3152.0
TD082	Total transport height, unladen	3152.0
TD034	Maximum external height, laden	3076.0
TD035	Frame height at theoretical rear wheelbase, unladen	1011.0
TD036	Frame height at theoretical rear wheelbase, laden	981.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	190.0
TD048	Lowering from driving position, rear	90.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-

Circle dimensions		m
TD055	Track circle diameter	13.6
TD056	Wall-to-wall turning circle diameter	15.3

Weights/loads		kg
TD026	Chassis weight with cab	8214.0
TD027	Chassis weight, front	---
TD028	Chassis weight, rear	---
TD029	Payload	---

TD018	Statutorily permissible gross vehicle weight	25000
TD025	Technically permissible gross vehicle weight	26000
TD031	Statutorily permissible gross train weight	0
TD032	Statutorily permissible trailer load	0

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.