

Model : TGS 41.400 8X4 BB-WW

Place of production:	MÜNCHEN
Vehicle model:	TGS 41.400 8X4 BB-WW
Basic vehicle	L 39W AE 05

Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005UP		Wheelbase 1795+3505+1400 mm
006CS		rear frame overhang 850 mm
018SI		engine D2066LF06 - 400 hp / 294 KW EURO2 - 1900 Nm Common-Rail
02AAG		Instrument panel km/h 'High-Line in colour'
021GG		Gearbox software MAN TipMatic Offroad (off-road deployment)
022QE		MAN TipMatic 12 28 OD gearbox
023EH		fuel tank 400l right
025ML		front axle VO-09/VO-09 straight
026EF		front springs parabolic 9,5 t
027AW		extended radiator and intercooler upto 35 degrees ambient temperature
028FP		rear springs parabolic 16 t
028PA		Fit tandem axles
029GC		Propshafts for high load profile
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034MH		hub-reduction rear axle HPD-1382/ HP-1352
035FA		Planetary axle ratio i = 4.83
037AC		with differential lock in rear axle
038GH		disc wheels 10 hole 11.75-22.5 on 1st FA TL
038JH		disc wheels 10-hole 11.75-22.5 on 2nd front axle TL
038PG		disc wheels 10-hole 9.00-22.5 on 1st RA TL
038RG		disc wheels 10-hole 9.00-22.5 on 2nd RA TL
038TG		disc wheel 10-hole 9.00-22.5 as spare wheel TL
042XY		without electronic tachograph
045CA		MAN EasyStart for TipMatic
05NAE		front panel unlockable from inside
050NN		M cab 2240mm wide, 1880mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality
058NH		driver's seat, high-comfort, with air suspension
059NA		co-driver's seat static, with longitudinal + seat back adjustment

080AE	door interior panelling washable
116AE	visco fan
116AZ	Fan control for use in hot countries
118AC	air deflector to stop dust swirling
118EK	Short mounting base (engine only)
118MA	EDC engine regulation
119EH	General PTO parameterisation
122S4	PTO NH/4C without horizontal flange f=1.14 on right
123CC	strainer for fuel tank
124AL	fuel filter
124AZ	Auxiliary fuel filter with water separator
150WR	Brushed aluminium insert on instrument panel
153KA	air conditioning system AC R134A without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194AB	operator's manual in English
201AR	air intake upswept with dry air filter / precleaner
201EM	Air filter cartridge with safety insert for heavy-duty deployment
201FA	fine dust and pollen filter
203EK	connection for external engine speedcontrol (ZDR)
205AN	air compressor 1-cylinder, 360 ccm
206EY	exhaust on rh side with tail pipe to rear
208AL	regulated rocker arm brake (EVBeC)
210XX	Without flame-start/jump-start system
211FB	Single-disc clutch DBE 430, reinforced
227AC	rear axle breather upswept
230AH	rear underride guard, round
230XW	Without front underride guard
230YX	without lateral underride guard
233EM	3-part steel bumper
234AX	towing coupling ROCKINGER SK5
236AF	cross member for trailer coupling
241AH	body attachment brackets bolted
245XX	without spare wheel holder
256AA	steering wheel lock
256EA	emergency steering pump
258HA	anti-lock braking system (ABS)
259CC	drum brake for front axle
259CE	drum brake for rear axle
262XX	without brake connection on frame end
272AT	Construction site step on front mudguard, driver's side
272FA	Entry lighting for driver and co-driver
276AC	Armrests for driver's seat
280AC	wiring for tank truck to ADR
280BA	Equipment for hazardous goods to ADR, type AT

280EU	stoneguard grille in front of radiator
281AB	medium-height design
283FB	Cab mounts on coil springs for 'M' cab
303AX	Lockable tank fastener - 1 u. ventilated for master key system
310EE	Halogen twin headlights H7 for right-hand traffic
310FA	2 spotlights on cab roof
311AA	protective grille for headlights headlights
311AE	protective grille for taillamps
318AA	marker lamps
318AK	lateral marker lights
319AR	reading lamp for driver
321EC	central locking
324AC	Two-tone horn,electric
325AA	MAN Tronic (on-board computer)
325EC	Language 1 'English' for display in instrument panel
325FE	Language 2 'French' for display in instrument panel
326XY	Without 12/24 V socket on end of frame
327AF	battery main switch, mechanical
329AS	Batteries 12 V 150 Ah, 2 units
329ER	Battery box up to 175 Ah
329HC	Maintenance sign for batteries - 'maintenance-free'
331AB	Basic alternator
339FP	Display on the dashboard for operating data
343AN	Acoustic warning system at end of frame for engaged reverse gear
345CV	Maximum electronic speed limitation 85 km/h
345EA	cruise control
346CA	charging pressure indicator
350NN	MAN Media Truck radio, 12 V with five-inch colour display
350XO	Without navigation SD
351US	AUX-IN/USB in the instrument panel
352DX	2 LED revolving beacons on cab roof,left and right
352WS	Revolving beacon, yellow
358AA	ETA electric cutout
362AH	Stabiliser on both rear axles
363AA	Stabiliser for front axle
370CM	air dryer
373AE	antifreeze effective down to -35 degrees
376XH	Without Mattress for lower bunk
376XK	Without Mattress for upper bunk
376XL	No bunks for 'M' , 'C', 'DK' cabs
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AS	Cab rear wall with 2 tinted windows,centre and right
381XC	Without curtain before bunks

381YX		Without all-roand curtain
382AA		Grille on rear window
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386XA		Without lifting roof
387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
388AK		sun shade in front of windscreen
388CC		Roller sunblind on driver's door
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
389CA		Grab handle on outside of cab roof, driver's side
390CT		cup holder in dashboard
390XX		without oddment box
392AH		kerb mirror, right
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
392XJ		Without front mirror on co-driver's side/at centre
394FM		1 Fire extinguisher, 2 kg, multilingual (English/German/Dutch)
400AH		mudflap front
401AS		mudguard cover for transfer
401CQ		Plastic mudguard rear (half-shell; without spray reduction)
401EL		3-part synthetic mudguards for 2nd front axle
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
405CP		20 m tyre inflator hose with pressure gauge
407AA		jack 25 t
411AA		1 chock
434CH		Smoking package
434DB		Interior design in Urban Concrete
44VCA		Crankcase ventilation closed
523AC		signs in English
538AE		plastic floor and engine tunnel covering
542FX		anti-noise measures are not in accordance with EU standard
542HS		aprons in wheel houses to prevent soiling of the engine
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
798LF		Height over cab, unloaded up to 4000mm
798WK		vehicle can be registered only as off-road vehicle to directive 70/156/EEC; note body
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006

LVS03		cab Pure white RAL 9010
80001		2 wahlweise 385/65R22,5 LENK-S+G TL
80002		2 wahlweise 385/65R22,5 LENK-S+G TL
90001		4 wahlweise 315/80R22,5 ANTR-S+G TL
90002		4 wahlweise 315/80R22,5 ANTR-S+G TL
90004		1 wahlweise 315/80R22,5 ANTR-S+G TL

Weights:

Gross weight: 44000

1st front axle: 9000

2nd front axle: 9000

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000