

MEILLER rear tipper H330 16 m³

Model

- MEILLER Classic rear tipper H330: H3TYPH330

Tipper body:

box-type tipper body inclined front wall and vertical tailgate side walls with robust, circumferential top border inclined towards the inside chamfered edges in the front to ensure a better flow of material

150 mm higher front wall scissors-type

stabiliser

supports made of abrasion-resistant, shock-proof rubber adjustable front supports

Subframe: welded box-type subframe made of high-strength fine-grained steel with longitudinal members, reinforced by a cross-type section at the rear

MEILLER hydraulic system:

oil tank, usable capacity of 60 litres

operating pressure 275 bar tipping

valve

- language on plates, lists and manuals: English (if available) H3SPR02
- suitable for a MAN chassis:

Veh. Basic	<ul style="list-style-type: none"> • sales name TGS new (V2020) • wheelbase 3,900/1,400 • cab OP2DL (cab NN) • exhaust OP1BG+OP1BQ (at side left) • air intake OP0AY (vertical) • emission standard Euro II/III • type OP2UN (tipper) • type of suspension leaf suspension • drive 6x4 	<p>H3FVKB25</p> <p>H3FRSD_390 0_1400</p> <p>H3FFHS42</p> <p>H3FAPU53</p> <p>H3FANS24</p> <p>H3FEUN03</p> <p>H3FART05</p> <p>H3FFED01</p> <p>H3FANT02</p>
Veh.Expert	<ul style="list-style-type: none"> • size of spare wheel 13 R 22,5 • ride height cab OPHBE (640 mm) • permissible GVW (in t) 33 t • prepar. pneum.control in cab OP3KN (tipper) • chassis overhang OP3EU (800 mm) • PTO unknown • OEM-supplied pump unknown • size of tyres rear axle 13 R 22.5 • mudguards rear axle OP1AO+OP1AY (RA 1/4-shell ÜP) • OEM-suppl.side underr.protect. OP1FG (w/o SUP) • OEM-suppl.rear underr.protect. OP1FD+OP1FU (RUP w/o extens.) • OEM-suppl. fix.elem. superstr. OPOX8 (fix.angles + guide pl.) 	<p>H3FFER03</p> <p>H3FFAH05</p> <p>H3FZGG03</p> <p>H3FPNE23</p> <p>H3FUBS54</p> <p>H3FNAB00</p> <p>H3FPUM99</p> <p>H3FREI03</p> <p>H3FKOT15</p> <p>H3FSSV09</p> <p>H3FUF518</p> <p>H3FBFA18</p>
Tipp. body	<ul style="list-style-type: none"> • side marker lamps OP2BJ (with SML) • OEM-supplied trailer coupling unknown • capacity 16 m³ • tipper body length 4,800 mm • tipper body width 2,300 mm • side wall height 1,400 mm • outside-positioned vertical top-hinged tailgate with grip lock (G1) • flush tailgate hinges • floor 8 mm HBW 450 (Hardox® 450 or equivalent material) • front wall 6 mm BS 70 side walls 6 mm BS 70 tailgate 6 mm BS 70 • cab protection up to upper cab edge (not in combination with sliding tarpaulin) 	<p>H3FSML10</p> <p>H3FAKU00</p> <p>H3VOL05</p> <p>H3KBL10</p> <p>H3KBB01</p> <p>H3BWH04</p> <p>H3RWF07</p> <p>H3RWL01</p> <p>H3BOD03</p> <p>H3WAN10</p> <p>H3DAC01</p>