

N. 1 BITUMEN/CUT-BACK (MC0)-EMULSION SPRAYING MACHINE Type 'SP/BE 100

The spraying tank will be installed on your chassis MAN TGM 4x2 WB 4425

TECHNICAL DESCRIPTION:

A) TANK CAPACITY 10.000 litres of Bitumen, cylindrical section, constructed using S235JR metal sheet, 4 mm. thickness, swelled bottom 4 mm.

thickness, Coating swelled bottom 3 mm. thickness, complete of:

- **basement in steel profile for fixing to vehicle chassis**
- **wave breakers within internal section**
- **man-hole ø 500mm, with ladder, service gang-way and breather**
- **level indicator**
- **bottom valve for emptying**
- **digital thermometer /thermostat for bitumen temperature control**
- **rock wool insulation 100 mm. thickness – density 100 Kg/m³**
- **external covering with ALLUZINK 10/10 thickness**
- **covering bottoms th. mm. 3**
- **roof-shield for instrument protection**
- **rotating beacon**

**B) DIESEL ENGINE, double-cylindrical, output power 28 HP./2000 r.p.m.,
tm LOMBARDINI/KOHERL, 'Tropicalized' type including :**

- **electrical starter**
- **single disc clutch with handle control**
- **electro-stop**
- **flexible coupling**

C) BITUMEN SUCTION PUMP – double inclination gears – mounted and submerged in the tank, in direct contact with the bitumen, including :

- **24.000 litres/hour output pump (400 lt/min)**
- **suction valve and output valve**
- **filter on suction line submerged**

- **D) GASOIL HEATING** with 'U' pipes consisting of:
 - stainless steel flue hat
 - automatic and pressurized burner Tm RIELLO– thermo power 100.000 Kcal/h, 24V
 - fuel tank 100 litres capacity for burner feeding, diesel engine, bitumen pump and spray bar washing
 - flexible hoses
 - stainless steel exhaust fumes hat
 - electrical panel fed by your vehicle
 - micro-switch on minimum level of bitumen

E) MANUAL SPRAYING HOSE, complete with :

- n. 2 nozzles
- ball valve ,driven by the handle
- flexible hose – 4 metres length – complete with threaded connections

F) SPRAYING BAR, bolted to tank basement, complete with:

- side arms manually extensible, folding type, with n. 24 spraying nozzles
- adjustable for various widths, from m. 2.50 to m. 4.00, with pneumatic piston
- nozzles spaced on 158 mm. centres on spraying bar
- device to adjust height of nozzles from ground level, through n. 2 telescopic screws
- control for the opening and closing of the taps for the application of the product to the nozzles.
- automatic return at interrupted spraying for the preheating of the bar and nozzles
- Nr.2 Inox flex pipes (delivery and return)
- nr.1 butterfly valve complete with pneumatic actuator

G) DIGITAL SENSOR:

- Digital Tachometer MPU
- Sensor to predetermine the quantity of bitumen and cut back to be sprayed

All mounted close to the truck driver

H) INSTALLATION ON YOUR VEHICLE with application of:

- mudguards
- rear lights adaptation
- splitting of loading weights on the axles
- speed limit adhesive disks
- yellow reflective tape
- reflective signs

