

Vehicle description for: TGM 18.250 4x2 BB CH



Illustration can deviate

١	10	h	ic	ما	sta	nc	lai	rde
V	æ	п	ш	æ	Sta	mc	ы	ros

iicie standai	ras	
	Product family	The new MAN Truck Generation
	Model & Variant	TGM 18.250 4x2 BB CH
	Vehicle type	Vehicle type, platform truck and chassis (LK)
	Cab	Compact CC cab
	Main wheel distance	4425 mm
	Overhang	2325 mm
	Steering configuration	Left

Vertical Load

	National Registration	Technical Load	
Gross weight	18,000 kg	18,600 kg	
Front axle	7,100 kg	7,100 kg	
Rear axle	11,500 kg	11,500 kg	

Horizontal Load

	National Registration	Technical Load
Gross train weight	0 kg	0 kg



The printed images in this offer are for explanatory purposes and may differ from the actual configuration. For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

	c characteristics	
_	Chassis	0P2U9
3	Chassis class, light/medium	0P2UB
1	Destination: Ghana (GH)	0P3GJ
1	Merchant tonnage 18 t	0P8LF
1	Basic layout of vehicle, all-round	0PGCU
1	Frame type, normal height	0P2TS
]	Vehicle type, platform truck and chassis (LK)	0P2UQ
]	Left-hand-drive	0P3AS
1	Right-hand traffic	0P3F5
1	Vehicle documents in English	0P2L7
1	Labelling in English	0P8NM
1	Cab position 530 mm (distance from frame lower edge to cab floor)	0PHBD
Pogi	stration	
legi I	stration Vehicle approval, N3 class	0P3JR
1	Maximum speed limiter, 85 km/h, electronic, engine speed regulation	0P2UI
1	Maximum vehicle noise level, 80 dB in acc. with UN/ECE-R 51.02	0PINC
1	Height over cab, unloaded up to 4,000 mm	0PHA1
1	Maximum vehicle width of 2,500 mm checked with respect to relevant cab components	0PIOH
1	Maximum vehicle width of 2,500 mm checked with respect to relevant chassis components	0PIOJ
ı	Maximum vehicle width of 2,500 mm checked with respect to relevant axles, rims, tyres, wheel trim	0PIOL
1	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW
٠	.monto	
JOCL	uments Without a sisteria and a superstation and is and	
]	Without registration documentation, national	0P3B0
		0P3B0
ppli	ication scope / transport tasks	
ppli	ication scope / transport tasks Vehicle version municipal/public service deployment	0P0H7
.ppli	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo	0P0H7 0P6WA
ippli	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal	0P0H7 0P6WA 0P2QS
ppli 1 1 1	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country	0P0H7 0P6WA 0P2QS 0PHIB
appli 1 1 1	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal	0P0H7 0P6WA 0P2QS
Appli	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country	0P0H7 0P6WA 0P2QS 0PHIB 0P4F0
appli	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country Case hardness of final drive Distribution	0P0H7 0P6WA 0P2QS 0PHIB
Appli	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country Case hardness of final drive Distribution s, editions and packages	0P0H7 0P6WA 0P2QS 0PHIB 0P4F0
appli	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country Case hardness of final drive Distribution s, editions and packages Special request paintwork	0P0H7 0P6WA 0P2QS 0PHIB 0P4F0
ppli ines loriz	Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country Case hardness of final drive Distribution s, editions and packages Special request paintwork Without Individual Lion package	0P0H7 0P6WA 0P2QS 0PHIB 0P4F0
appli	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country Case hardness of final drive Distribution s, editions and packages Special request paintwork Without Individual Lion package	OPOH7 OP6WA OP2QS OPHIB OP4F0 OPJTD OPJT1
ppli ines loriz ines ines	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country Case hardness of final drive Distribution s, editions and packages Special request paintwork Without Individual Lion package zontal and vertical loads 18,000 kg permitted gross load, vertical, nat. appr.	OPOH7 OP6WA OP2QS OPHIB OP4F0 OPJTD OPJT1 OP5PB
appli	ication scope / transport tasks Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country Case hardness of final drive Distribution s, editions and packages Special request paintwork Without Individual Lion package zontal and vertical loads 18,000 kg permitted gross load, vertical, nat. appr. 18,600 kg permitted gross load, vertical, tech. 18,600 kg permitted gross load, vertical, tech. Plus	0P0H7 0P6WA 0P2QS 0PHIB 0P4F0 0PJTD 0PJTD 0PJT1 0P5PB 0P5S7 0P8GT
appli	Vehicle version municipal/public service deployment Distribution transport, general cargo 060 Box body, universal Temperature range, vehicle deployment, warm country Case hardness of final drive Distribution s, editions and packages Special request paintwork Without Individual Lion package zontal and vertical loads 18,000 kg permitted gross load, vertical, nat. appr. 18,600 kg permitted gross load, vertical, tech.	0P0H7 0P6WA 0P2QS 0PHIB 0P4F0 0PJTD 0PJT1 0P5PB 0P5S7



_		
_	11,500 kg permitted load on rear axle NatZu	0P5G7
_	11,500 kg permitted load on rear axle, tech.	0P5IJ
_	11,500 kg permitted load on rear axle, tech. Plus	0P8BN
	0kN D value	0P8XD
Notif	fication texts	
	Without note (propshaft wear)	0PJRV
	,	
Cha	assis	
Vehi	cle frame (wheelbase, overhang,)	
	Main wheelbase, 4,425 mm	0P2ZV
	Frame overhang, rear, 2,325 mm	0P3DT
	Main frame side member thickness, 7 mm	0P0Y5
	Vehicle rear, straight end of frame	0P0XT
	aust system, air intake	
	Exhaust silencer, side, right	0P1BH
	Exhaust tailpipe, towards middle of frame	0P1BT
	Air intake, behind cab, raised	0P0AY
Batte	ery cases, batteries, alternator	
	2 batteries, 12 V, 180 Ah, long-life (EFB), maintenance free	0PGB1
	Alternator, Basic	0P1BV
	Medium battery box, 2 batteries	0P0WU
	Battery box, left	0P0WO
	Main battery switch, mechanical	0P0WF
	Fuses	0P1V1
Tool	co and final line	
_rank	s and fuel line Fuel tank capacity 150 I, right	0P4DZ
_	Fuel tank, right, steel	0P4GN
_	Tank cross-section, right, low	0P4HF
_	AdBlue tank capacity 35 l, right	0P4CZ
_	AdBlue tank, right, plastic	0P4HU
_	Fuel tank cap, lockable for master key system	0P4H5
_	Cap for AdBlue tank, lockable	0P4GE
	Fuel pre-filter on the frame	0PKN2
Fran	ne attachments	
	Underride protection, front	0P1FN
	Without working platform	0P0VH
	Without underride protection, side	0P1FG
	Spare wheel hoist on left side, in front of rear axle	0P0XO
	Hoist for spare wheel	0P0VN
	Final cross member, with hole pattern 160 x 100 mm	0P1SB
	Underride protection, rear, round	0P1FD
	Wheel chock, 1 unit, with retaining device	0P1FO
	Without body attachment brackets/thrust plates	0P0X6



Pneı	ımatic brakes, compressed-air generation, brake system	
	Air compressor, 1-cylinder, 238 ccm	0P0AD
	Compressed-air treatment, pneumatically controlled	0P0AB
	Steel compressed-air tank	0P0XH
	Electronic brake system (EBS)	0P0BL
	Anti-lock braking system (ABS)	0P0BE
	Full brake assistant	0P0CM
	Without preparation for EBS Full control unit	0PHPM
	Engine brake, exhaust flap	0P0BU
	Disc brakes on front axle	0P1I9
	Disc brakes on rear axle	0P1I4
	Parking brake control, next to driver's seat	0P3KH
	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
	Brake lining thickness display, with brake lining wear warning	0P0BG
	Harmonisation of brake lining wear	0P0BI
Light	s and acoustic signals on the chassis (rear lights,)	
	Rear lights	0P2AQ
	Acoust. Reversing warning system when reverse gear selected	0P3CD
	Light function test	0P2AD
	No side marker lights	0P2BK
Driv	eline/running gear	
Engi	ne, radiator	
	Diesel engine MAN D0836 LFL95, 184 kW (250 hp) output, 1,050 Nm torque, Euro 4	0P5ZG
	Fuel filter, heated, for fuels up to Cleanliness Class 25	0PHIG
	Fuel pre-filter, with oil separator/water trap, heated	0P0AU
	Without torque reduction	0P0G5
	Engine dry-air filter, with safety insert	0P0B8
	Ventilation, crankcase, closed	0P8PM
	Anti-noise skirt, engine	0P2E7
	Engine cooler, normal length	0P4XX
	Engine oil dipstick	0P0B5
	Antifreeze, down to -32 °C	0P0AK
	Service product level indicator and intake system vacuum	0P3KT
	box, clutch	ADEL (D
	MAN TipMatic 12.12 OD	0P5VP
0	MAN TipMatic 12.12 OD Gearbox for normal percentage of overrun during driving operation	0PGDA
0	MAN TipMatic 12.12 OD Gearbox for normal percentage of overrun during driving operation MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0PGDA 0P3KI
0	MAN TipMatic 12.12 OD Gearbox for normal percentage of overrun during driving operation MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option) MAN Idle Speed Driving gearbox function	0PGDA 0P3KI 0P0ER
0 0 0	MAN TipMatic 12.12 OD Gearbox for normal percentage of overrun during driving operation MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option) MAN Idle Speed Driving gearbox function MAN TipMatic Efficiency driving program, up to 70,000 kg	0PGDA 0P3KI 0P0ER 0P0FA
0	MAN TipMatic 12.12 OD Gearbox for normal percentage of overrun during driving operation MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option) MAN Idle Speed Driving gearbox function	0PGDA 0P3KI 0P0ER
0	MAN TipMatic 12.12 OD Gearbox for normal percentage of overrun during driving operation MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option) MAN Idle Speed Driving gearbox function MAN TipMatic Efficiency driving program, up to 70,000 kg	0PGDA 0P3KI 0P0ER 0P0FA



Front axle tyres Michelin 295/80R22.5 WORKS Z Steering-Road+Offroad TL 0PEVZ



Delegated Regulation (EU) 2020/740 Supplier name or trademark	MICHELIN
Commercial name or trade designation	X WORKS Z VM
Model identifier	363450
Tyre size designation	295/80R22.5
Load-capacity index	152
Load-capacity index (Load index for Dual mounting)	149
Speed category symbol	K
Fuel efficiency class	D
Wet grip class	В
External rolling noise class	A
External rolling noise value	68
Severe snow tyre	No
Date of start of production	39/12
Date of end of production	
Additional information	295/80R22.5 X WORKS Z TL 152/149K VM MI
Load-capacity index (Single Load index for additional service description)	154
Load-capacity index (Dual Load index for additional service description)	150
Speed category symbol (for Additional Service Description)	1

Rim type, front axle, steel, single-part	0P0P0
Rim size, front axle, 10-hole, 9.00x22.5	0P0NI
Wheel nut cover ring, front axle	0P0PR
Rear axle tyres optionally 295/80R22.5 Drive-Road+Offroad TL (152/148 K)	0PDPD
Rim type, rear axle, steel, single-part	0P000
Rim size, rear axle, 10-hole, 8.25x22.5	0P0MQ
Spare wheel, in accordance with configuration for front axle tyres	0P0MH
Centring sleeves for rim mounting	0PHZW

F	١x١	es

AXIE	AXICS				
	4x2	0P3B1			
	Steering ratio, standard	0P1JX			
	Steering oil tank with dipstick	0P1JW			
	Front axle, 7,500 kg, not driven, cranked, steered, not liftable	0P5EQ			
	Mudguard, front axle	0P1AT			



		an () (a
	Splash guard mat on mudguard, front axle, longer at bottom	0P1XS
3	Rear axle, 11,500 kg, HY axle without drive shaft, straight, not steered, not liftable	0P4ZL
-	Twin tyre on rear axle	0P1HN
_	Axle ratio, i = 4.63	0P0D9
_	Differential locks on driven rear axles	0P0DI
	Without differential locks, front axles	0P0DL
Axle	control system and suspension	
	Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
	Leaf-spring suspension on front axle, parabolic, 1-leaf, steel	0P1JC
	Leaf-spring suspension on rear axle, parabolic, 4-leaf, steel	0PGBF
-	Spring load-bearing capacity front axle 7,100 kg	0P5CY
_	Spring load-bearing capacity of rear axle, 11,500 kg	0P5BT
-	Shock absorbers on front axle	0P1M4
_	Shock absorbers on rear axle	0P1LQ
0	Stabiliser, front axle	0P1LD
-	Stabiliser, rear axle	0P1LA
	Axle location system not as wishbone	0P6ZY
	Without trailer air suspension control	0PHN2
Cab	and cab exterior	UBSUK
Cab	Compact CC cab	0P2DK 0P1V8
Cab	Compact CC cab Cab mount, Basic	0P1V8
Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual	0P1V8 0P1V6
Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof	0P1V8 0P1V6 0P1VY
Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic	0P1V8 0P1V6 0P1VY 0P1SD
Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE
Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0
Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK
Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual	0P1V8 0P1V9 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ
Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units	0P1V8 0P1V7 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS 0P3JT 0P1WV
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1US 0P3JT 0P1WV 0P2DQ
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle Door windows, tinted	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS 0P3JT 0P1WV 0P2DQ 0P1WO
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle Door windows, tinted Door window, safety glass	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS 0P3JT 0P1WV 0P2DQ 0P1WO 0P1WM
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle Door windows, tinted	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS 0P3JT 0P1WV 0P2DQ 0P1WO
Cab	Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle Door windows, tinted Door window, safety glass	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS 0P3JT 0P1WV 0P2DQ 0P1WO 0P1WM
Cab Cab Cab Cab Cab Cab Cab Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle Door windows, tinted Door window, safety glass Cab rear wall, no window	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS 0P3JT 0P1WV 0P2DQ 0P1WO 0P1WM
Cab Cab Cab Cab Cab Cab Cab Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle Door windows, tinted Door window, safety glass Cab rear wall, no window s and acoustic signals on cab exterior (headlights, horn,)	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1WS 0P3JT 0P1WV 0P2DQ 0P1WO 0P1WM
Cab Cab Cab Cab Cab Cab Cab Cab	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle Door windows, tinted Door window, safety glass Cab rear wall, no window s and acoustic signals on cab exterior (headlights, horn,) Without light and headlight package	0P1V8 0P1V6 0P1VY 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1UZ 0P1WS 0P3JT 0P1WV 0P2DQ 0P1WO 0P1WM
	Compact CC cab Cab mount, Basic Cab tilt mechanism, manual No tilting roof/sliding roof Bumper, plastic Front step, integrated, with grab option Windscreen, composite safety glass, tinted Sunblind, in front of windscreen Wiper system for windscreen Wiper activation, manual Step unit, rigid Central locking, no remote control Vehicle key, 2 units No door extension Door labelling, according to trade tonnage of vehicle Door windows, tinted Door window, safety glass Cab rear wall, no window s and acoustic signals on cab exterior (headlights, horn,) Without light and headlight package Front headlights, H7	0P1V8 0P1V6 0P1V7 0P1SD 0P1VE 0P1X0 0P1WK 0P1WG 0P1UL 0P1UZ 0P1UZ 0P1WS 0P3JT 0P1WV 0P2DQ 0P1WO 0P1WM 0P1VD



	Contour lights, bulb, 2 units	0P2BT		
	Turn signal lights, sides, bulb	0P1Z6		
	Horn, two-tone, electrical	0P1W1		
	Preparation for loading area lighting	0P2A5		
	Without revolving beacons at the rear of the vehicle	0PJRO		
	ors and mirror replacements			
	Exterior rear-view mirror, mechanically adjustable	0P2CC		
	Mirror housing, not painted	0P2CP		
	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT		
	Kerb mirror, right, mechanically adjustable	0P2CH		
	Front mirror, mechanical adjustment	0P2CJ		
	Without mirror package	0PKWV		
Coot	_			
Seat:	Seat covers, fabric, standard	0P2PQ		
	Comfort driver's seat, air-sprung	0P2P2		
	Co-driver's seat, not sprung, length and backrest adjustment	0P2OQ		
	Indicator, seat belt, 1st row of seats, acoustic and visual	0P8L1		
_	Without driver's seat package	0PKXV		
	Without co-driver's seat package	0PKXU		
Drive	Driver's workplace			
	Multi-function steering wheel, adjustable height and angle	0P2GD		
	Steering wheel, with parking position	0P2GE		
	Steering lock	0P3JZ		
	Instrumentation, Basic km/h	0P3L3		
	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY		
	Tachograph, calibrated	0P2KG		
	Plug-in ashtray, instrument panel in middle section, 1 unit	0P2FO		
	Cigarette lighter	0P2IH		
	Single DIN slots, 4 units, roof space, front	0P2FJ		
	Without storage tray next to seat	0PJRS		
	air-conditioning system	ODONILI		
	Air-conditioning system, manual	0P2NU		
Bunk	x area			
	Without bunk area	0PKFY		
	interior			
	Colour scheme for interior styling, dark	0P2I6		
	Interior styling analogous to colour scheme	0PGBT		
	Windscreen roller blind, internal	0P2FE		
	Interior light, central	0PHA6		
	Reading light, 1 unit, driver's side	0P2IQ		
	Entry lighting	0P2IO		
	Door interior cladding, washable	0P2IA		
	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2		



	Entry handles, standard	0PHPK
	Without driver's workplace package, Comfort	0PKXT
	Interior light, reading light (driver's side)	0PKMY
	Without stowage and storage space package	0PKXS
٨٥٥٥	essories and tools	
ACCE	Jack, 10,000 kg	0P3F7
_	Without accessories and tools package	0PKXA
_	Vehicle toolkit	0P2TX
_	No warning triangle	0P3FH
Intel	lligent Truck	
	ingent riuck	_
Assis	stance systems	
	Tempomat (cruise control, CC)	0P1TR
	Without advanced emergency braking system	0P1U5
	Without driving fitness detection system	0PHN5
	Without Front Detection	0PHNA
	Without traffic sign recognition	0PHNE
	Without Reversing Motion System	0PHNV
	Without distance warning system	0PKA0
Infota	ainment (radio,) MMT infetairment system. Starter Resig	0P2M1
	MMT infotainment system, Starter Basic MAN loudspeaker system	0P2MF
	No navigation map	0P2N2
_	No navigation map	OFZINZ
Bod	lies/interfaces	
Interi	faces to semitrailer (e.g. fifth-wheel coupling, brake connection,)	
	Without trailer brake connection behind cab	0P1O3
	No fifth-wheel coupling	0P1RJ
	Without sensing of the fifth-wheel coupling	0PHN7
_	alectosilenig et ale mai mise esuping	· · · · · ·
Inter	faces to trailer (e.g. trailer coupling, brake connections,)	
	Towing coupling at final cross member, RINGFEDER type 6451	0P1MY
	Towing coupling on final cross member	0P1SH
	Without trailer brake connection at end of frame, centre	0P1O0
	Without trailer socket at frame end	0P1OW
	Without trailer socket for anti-lock brake system (ABS)	0P1O9
	orks bodies and interfaces to bodies (e.g. tipper indicator)	
	Interface for data exch. with body (customer-specific control module) and engine intermediate speed control (ZDR), front area of cab	0P2NA
	Speed control (ZDIV), front area of cab	
РТО	S	
	Without fan wheel for PTO, gearbox-dependent	0P4VR
	Preparation, electr., for subsequent installation of a shiftable PTO, gearbox-dependent	0P4OI



	Sector-specific parameterisation for refuse collector vehicles, side loaders (w control)	orking speed 0P4X8	
Tow	ing, recovery and lashing		
	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK	
Pair	ntworks		
Pain	twork, cab, top		
	Top coating, cab	0P6YB	
Pain	twork, cab, bottom		
	Textured coating, step units	0P6X9	
	Textured coating, mudguard, behind cab	0P6YG	
	Textured coating, bumper, plastic	0P6YP	
Pain	twork, chassis		
	Top coating, chassis	0P6YC	
	Top coating, rims, steel, white-aluminium	0P6YL	
Col	our		
	Top coating, cab	JRE WHITE RAL 9010	N
	Top coating, chassis GR	RAPHITE BLACK RAL 9011	N



Technical data: TGM 18.250 4x2 BB CH / L08DAA04

	type: Vehicle type, platform truck and chassis	(LK)
	ompact CC cab	
Drive T	ype: 4x2	
Length	s	mm
TD071	Total length	8447.0
TD063	Front vehicle overhang	1532.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	0
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2325.0
TD072	Distance from first front axle to body	441.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	
TD068	Coupling length	8127.0
Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0
Frame		mm
	Frame width at front	964.0
TD010	Frame width at the rear	864.0
TD078	Frame profile	270 x
	·	70 x 7
Heights	 S	mm
	Maximum external height, unladen	2949.0
	Total transport height, unladen	2949.0
TD034	Maximum external height, laden	2873.0
TD035	Frame height at theoretical rear wheelbase, unladen	1107.0
TD036	Frame height at theoretical rear wheelbase, laden	976.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-
	dimensions	m
TD055	Track circle diameter	15.4
TD056	Wall-to-wall turning circle diameter	16.9
Weight	s/loads	kg
	Chassis weight with cab	5342.0
TD026		
TD026 TD027		
TD027		

TD018	Statutorily permissible gross vehicle weight	18000
TD025	Technically permissible gross vehicle weight	18600
TD031	Statutorily permissible gross train weight	0
TD032	Statutorily permissible trailer load	0

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.