

## Model : TGS 33.360 6X4 BB-WW

Vehicle TGS 33.360 6X4 BB-WW

### Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005NW		wheelbase 3900+1400 mm
006LY		rear frame overhang 2050 mm
018IZ		Engine D2066LF48 - 360 HP / 265 KW EURO3 - 1800 Nm common rail
02AAG		Instrument panel km/h 'High-Line in colour'
021GP		Gearbox software MAN TipMatic Profi (road deployment)
022QE		MAN TipMatic 12 28 OD gearbox
023EH		fuel tank 400l right
025MK		front axle VO-09 straight
026EC		front springs parabolic 8.0 t
027AN		radiator and intercooler for up to 35 degrees ambient temperature
028EC		rear springs parabolic 13 t
028PA		Fit tandem axles
029GC		Propshafts for high load profile
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034MH		hub-reduction rear axle HPD-1382/ HP-1352
035LF		Planetary axle ratio i = 4.33
037AC		with differential lock in rear axle

038GG		disc wheels 10 hole 9.00-22.5 on 1stFA TL
038PG		disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG		disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038TG		disc wheel 10-hole 9.00-22.5 as spare wheel TL
042FP		EC tachograph electronic - 2 driverswith add. recorder, for tankers
045CA		MAN EasyStart for TipMatic
05NAE		front panel unlockable from inside
050NF		L cab 2240mm wide, 2280mm long
052AE		Storage box accessible from outside - flap unlocked from inside
058BC		seat coverings in high-comfort quality
058NH		driver's seat, high-comfort, with air suspension
059NA		co-driver's seat static, with longitudinal + seat back adjustment
064AC		two additional vehicle keys
068AS		door extension
080AE		door interior panelling washable
116AE		visco fan
116AZ		Fan control for use in hot countries
118AC		air deflector to stop dust swirling
118EK		Short mounting base (engine only)
118MA		EDC engine regulation
119EH		General PTO parameterisation
122S4		PTO NH/4C without horizontal flange f=1.14 on right
123CC		strainer for fuel tank
124AL		fuel filter
124AZ		Auxiliary fuel filter with water separator
150MC		Window cleaning set
150WR		Brushed aluminium insert on instrument panel
153KA		air conditioning system AC R134A without CFHC
159XS		without cab insulation NORDIC (against cold) for M, L and LX cab
194AC		operator's manual in French
197SL		Mirror trim cover painted in cab colour
201AR		air intake upswept with dry air filter / precleaner
201EM		Air filter cartridge with safety insert for heavy-duty deployment
201FA		fine dust and pollen filter
203EK		connection for external engine speedcontrol (ZDR)
203ES		Control module for external data exchange (customer-specific control module) with fleet management system in
205AN		air compressor 1-cylinder, 360 ccm
206ET		exhaust on lh side with tail pipe towards rear
208AK		exhaust valve brake
210XX		Without flame-start/jump-start system
211FD		Single-disc clutch DBE 430
227AC		rear axle breather upswept

230AH		rear underride guard, round
230XW		Without front underride guard
230YX		without lateral underride guard
233EM		3-part steel bumper
234AX		towing coupling ROCKINGER SK5
236AF		cross member for trailer coupling
241AH		body attachment brackets bolted
245AV		spare-wheel holder on right side behind rear axle
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)
259CC		drum brake for front axle
259CE		drum brake for rear axle
262XX		without brake connection on frame end
272FA		Entry lighting for driver and co-driver
276AC		Armrests for driver's seat
278EA		Air connection in cab
278EF		Air lines and air gun
280AC		wiring for tank truck to ADR
280BD		Dangerous goods equipment in accordance with ADR Type EXIII (EXII, FL, AT)
280EU		stoneguard grille in front of radiator
281AB		medium-height design
282CH		fire apron for tanker
283FS		Cab mounts on coil springs for 'L,LX,XL,XLX,XXL' cab
303AT		Non-lockable tank cap 1 u. non-ventilated (not eligible for approval/registration according to ECE-R34)
310EE		Halogen twin headlights H7 for right-hand traffic
310FA		2 spotlights on cab roof
311AA		protective grille for headlights headlights
311AE		protective grille for taillamps
318AI		LED clearance lamps
318AK		lateral marker lights
319AR		reading lamp for driver
321EC		central locking
324AC		Two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EE		Language 1 'French' for display in instrument panel
326CK		trailer socket for anti-skid system on frame end
326XY		Without 12/24 V socket on end of frame
327CA		battery emergency cutout
329AS		Batteries 12 V 150 Ah, 2 units
329ER		Battery box up to 175 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331AB		Basic alternator

339FP		Display on the dashboard for operating data
343AN		Acoustic warning system at end of frame for engaged reverse gear
345CV		Maximum electronic speed limitation 85 km/h
345EA		cruise control
346CA		charging pressure indicator
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350XO		Without navigation SD
351US		AUX-IN/USB in the instrument panel
352DX		2 LED revolving beacons on cab roof, left and right
352WS		Revolving beacon, yellow
358AA		ETA electric cutout
362AF		Stabiliser on 2nd rear axle only
363AA		Stabiliser for front axle
370CM		air dryer
373AE		antifreeze effective down to -35 degrees
376FA		1 bunk with storage space (with aluminium frame).
376HA		Mattress for lower bunk
376XK		Without Mattress for upper bunk
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-round curtain
384AS		Automatic seat belt in red
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386AS		Mechanical lifting roof
387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
388AK		sun shade in front of windscreen
388CA		Roller sunblinds on both doors
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390CT		cup holder in dashboard
390XB		without pigeon hole on rear wall
390XX		without oddment box
392AH		kerb mirror, right
392CL		EU front mirror on co-driver's side
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
394FE		1 French fire extinguisher, 2 kg to 1996 safety regulations
400AH		mudflap front
401AS		mudguard cover for transfer

401CQ		Plastic mudguard rear (half-shell; without spray reduction)
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405CK		Omission of hazard warning lights
405CP		20 m tyre inflator hose with pressure gauge
407AH		jack 12 t
411AA		1 chock
411AC		2nd chock
434DB		Interior design in Urban Concrete
44VCA		Crankcase ventilation closed
523AE		signs in French
523CA		warning sign at rear
538AE		plastic floor and engine tunnel covering
542BT		ADR inspection and certificate
542FX		anti-noise measures are not in accordance with EU standard
542HS		aprons in wheel houses to prevent soiling of the engine
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
798LF		Height over cab, unloaded up to 4000mm
798WF		vehicle cannot be registered to directive 2000/40/EC. Exceptions possible under cert. circumstances.
LQA08		steel bumper in 2-pack acrylic
LQA46		mudguards behind cab in 2-pack acrylic
LQA49		Door extension and step units, 2K acrylic
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Pure white RAL 9010
LVS08		bumper Pure white RAL 9010
LVS46		mudguards behind cab Pure white RAL 9010
LVS49		door extension and steps Pure white RAL 9010
80001		2 wahlweise 315/80R22,5 LENK-S+G TL
90001		4 wahlweise 315/80R22,5 ANTR-S+G TL
90002		4 wahlweise 315/80R22,5 ANTR-S+G TL
90004		1 wahlweise 315/80R22,5 LENK-S+G TL

**Weights:**

Gross weight: 33000

1st front axle: 8000

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000

Trailing axle: 0