

---

**4 Piece      SCHMITZ CARGOBULL insulated box body - FERROPLAST - V7**  
BOX - COOL V7 - for truck chassis with THERMO KING T 800R

---

**Dimensions and weights**

Internal length	ap.	6.050 mm	Total tare weight	+/- 3%	2.704 kg
Internal width	ap.	2.490 mm	Overall length	ap.	6.200 mm
Internal height	ap.	2.250 mm	Overall trailer width	ap.	2.600 mm
Usable internal length	ap.	6.050 mm	Door aperture height	ap.	2.240 mm
Usable internal height	ap.	2.250 mm	Door aperture width	ap.	2.490 mm
Total height at front (unladen)	ap.	2.509 mm			
Total height at rear (unladen)	ap.	2.509 mm			

Special requests are not considered in the above mentioned dimensions and weights.

---

**Chassis**

**CARGOBULL \*\*\* HIGHLIGHTS \*\*\***

**C00275      Production PANEVEZYS**

**Registration/Certification**

**P02190      2 warning plates to rear 565x132 ECE-R70 yellow/red stripes; vertical on rear wall**

**X91012      Country of registration: "the Netherlands"**

**X90520      Intern. custom seal (TIR) for body with rear door, without TIR certificate (f.KR.)**

**Chassis**

M00300      no provision for trailer traffic

C20002      Without rear underrun bar (available on the truck)

X00101      Without side guard acc. RL 89/297EWG (in existence of truck)

#### Sub frame

- C00482** Subframe bolted and galvanized , incl assy material, 6050 BOX, COOL  
C00524 Provision for sub frame in normal heights

#### Light system

- E00096 Without side tracking lights  
K75086 Switch for interior light at the rear, under the floor  
C24022 Without lamp holder and number plate holder for truck  
E00223 Without side marker lights (in existance at the truck)  
K75101 2 white front top position marker lights, 2 red rear top position marker lights

#### Spray suppression

- P00965** Straight plastic mudguard, kit  
**P00706** Anti-spray mud flaps with Schmitz Cargobull logo, side spray guard

#### Further chassis equipment

- X10648** Plastic tool box complete with inlay floor & drawer, kit  
P02020 2 rear corner rubber block buffers  
P02024 1 rear rubber buffer across rear width  
C90026 1 telescopic ladder at rear, kit

#### Tail-Lift

- L10010 Without provision for tail lift.

---

### Bodywork

#### Body

- K00001 PU foam panel, free of thermal bridges, sealed against vapour diffusion  
**K00856** BOX COOL V7, internal length 6050 mm  
**C00474** Box loading  
K09001 Inner skin is 0.6mm PVC coated steel scuffproof and load safe

#### Front bulkhead/Roof/Side walls

- K21020 Insulated front bulkhead, NX17 foam, with reinforcement for fridge installation  
K42010 FP insulated sidewall, COOL 45, NX17 foam  
**K62004** FP strong insulated roof, NX17 foam  
**K72301** Row(s) recessed galvanized load restraint track to both walls,without side door-6050  
Floor to middle of 1st load securing rail 1.200 mm

#### Rear closure

- K31050 FP 2-wing rear door, insulated, NX17 foam, with simple stainl. steel locking mechanism  
**K56005** Rear wall door -Emergency opener from inside, rotatable design  
K39013 Rear frame is stainless steel, sand blasted finish  
K73311 300mm depth, anodized aluminium kick strip fitted at base of each rear door  
P02040 Hinge protection rubber buffers fitted vertically to lower part of the rear frame  
P02071 Without add. buffer protection to rear frame across bottom

#### floor

- K11104** 2 drains with taps at the rear of the floor with extended hoses  
K11151 Aluminium barley seed floor, low noise Test load 5500 kg V7  
K12001 300mm aluminium kick strip at front and both sides welded to floor

#### Further body equipment

- K72466 without multifunction clamping bars  
**K75113** Particularly bright LED lighting inside the box  
**K72427** 2 x Rounded steel telescopic locking bar (galv. steel) horizontal, with pins on both sides  
K72440 Without tension belt for load securing rail  
K72448 Without tension belt for double stack system  
**K92002** Plastic curtain for the entire rear door

#### Cooling unit

<b>K91538</b>	<b>Door contact switch for cooling unit ON/OFF coupled with roller shutter / rear wall door</b>
K80573	provision for THERMO KING T-800R
K80001	Fridge unit aperture cut out and bolt holes drilled in front bulkhead
<b>K80003</b>	<b>With cover for bulkhead cut out</b>
<b>K81331</b>	<b>THERMO KING T-800R 50 with Battery and Battery box</b>
<b>K80169</b>	<b>Cooling unit packed and loaded in the body</b>
<b>K91409</b>	<b>Provision for temperature recorder Euroscan RX3 (only for ATP application)</b>
<b>K80123</b>	<b>Remote control for cooling unit, KIT</b>

#### Painting/Finishing

K99204	Roof painted in SCB 9010 white
X90340	Partial contour marking, side, white, rear red all around
K99050	Body finished in white SCB 9010
X90199	Without lettering

#### Special request

(not included in the above mentioned dimensions and weights)

K11107	2 drains with taps at the front of the floor with extended hoses	1 Piece
SON001	20m extension cable electric run CU	1 Piece
K80229	Flat fuel tank approx. 90 l; front filler overhang increased by 60 mm.	1 Piece
K91376	Temperature recorder Touch Log Premium with printer, according to EU dir. 12830	1 Piece
X90310	Provision ATP IR - certification w/o decals, w/o ATP-type plate (B)	1 Piece
X91500	Body certified to HACCP regulations , incl. HACCP cert. and decal on front bulkhead	1 Piece
SON005	ATP test due to Length / 4 drains	1 Piece

Optional equipment is not included in the technical specification.

#### Finishing / Colour specification

Part	Color	Number	Classification
Body	SCHMITZ WHITE	9010	SCB
Roof	SCHMITZ WHITE	9010	SCB