

Model: TGS 18.500 4X4 BB

Vehicle model: TGS 18.500 4X4 BB

Basic vehicle: L 52S SJ 03

Technical extent of delivery

Code Customer

Special Request

Designation

001AA		steering arrangement. left
005BK	X	wheelbase 3600 mm
006NM	X	rear frame overhang 2250 mm Erstmuster
018G4		engine D2676LF66 - 500 hp / 368 kW EURO6 SCR - 2500 Nm C-R OBO-C w/o torque red.;spec case app, req.
02AAG		Instrument panel km/h 'HighLine in colour'
021GH		Gearbox software MAN TipMatic Emergency [emergency services vehicles in off-road deployment)
022QE		MAN TipMatic 12 28 OD gearbox
023JX	X	Fuel tank, aluminum 200l left and 35l AdBlue
025MS		front axle VP-09 driven
026EF		front springs parabolic 9,5 t
027AW		extended radiator and intercooler upto 35 degrees ambient temperature
028EB		rear springs parabolic, 11.5 t
03KAA	X	fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034ML	X	hub-reduction rear axle HP-1342 single tyred
035FA		planetary axle ratio $i = 4.83$
037AC	X	with differential lock in rear axle
037CB		differential lock in front axle with buzzer
037CM		restricted steering control when FA diff. lock is engaged
038EW	X	disc wheels 10-hole 10.00-20 on 1st FA TL
038FQ	X	disc wheel 10-hole 10.00-20 as spare wheel TL
038FX	X	disc wheels 10-hole 10.00-20 on 1st RA TL for single tyres
042DM		Digital tachograph made by MAN
05NAE		front panel unlockable from inside
050NN		M cab 2240mm wide. 1880mm long
052XA		without stowage boxes
058BC		seat coverings in high-comfort quality
058NR		Air-sprung comfort drivers seat. with lumbar support, shoulder adjustment and heating
059NA		co-driver's seat static, with longitudinal + seat back adjustment
080AE		door interior paneling washable
116AE		visco fan
116EK		heat exchanger for gearbox
118AC		air deflector to stop dust swirling
118EK		Short mounting base (engine only)
118MA		EDC engine regulation.

119EH		General PTO parameterization
119NB		Emergency brake signal (ESS)
120AX		double flange coupling. elastic
120KH		PTO at flywheel end with 6-hole flange (100D) f=1.233 900 Nm continuous load – 1000 nm brief load
121FS		Gearbox functionality: Rock-free mode
123HE		U-parts for fuel tank
124AL		fuel filter
124AT		Heated additional fuel filter / water trap
124EA		fuel filter heating
142AF		calibrate tachograph
146AH		front wheel drive, permanent
146KA		transfer case G172
150MC		Window cleaning set
150WR		Brushed aluminum insert on instrument panel
153EY		air auxiliary heater EBERSPACHER D4S
153KA		air conditioning system AC R134A without CFHC
159XS		without cab insulation Nordic (against cold) for M, L and LX cab
194AV		operator's manual in RUMANIAN
201AS		air intake raised with dry air filter
201FA		fine dust and pollen filter
203EK		connection for external engine speed control (ZDR)
203ER		Control module for external data exchange (customer-specific control module) with body functionality
205AN		air compressor 1-cylinder, 360 ccm
206KF	X	Exhaust on right with bottom outlet, moved back
208AL		regulated rocker arm brake (EVBeC)
210AA		flame starting system
211FB		Single-disc clutch DBE 430. reinforced
227AA		front axle breather support
227AC		rear axle breather upswept
230XW		Without front underride guard
230XX		Without rear underride guard
230YX		without lateral underride guard
233EM		3-part steel bumper
234HC		2 shackles at front end of frame
236AF		cross member for trailer coupling
241AC		without platform mounting brackets
245XX		without spare wheel holder
256AF		steering wheel lock with immobilizer
258HA		anti-lock braking system (ABS)
259CC		drum brake for front axle
259CE		drum brake for rear axle
262XX		without brake connection on frame end
272FA		Entry lighting for driver and co-driver
276AC		Armrests for driver's seat
28OAC		wiring for tank truck to ADR
280EU		stone guard grille in front of radiator
280HD		Engine start/stop device under front panel
281AA		high design

283FB		Cab mounts on coil springs for 'M' cab
284LU		Switch position DS leads to increased fuel consumption as well as wear to the driveline incl. clutch
303AX		Lockable tank fastener - 1 u. ventilated for master key system
303CC		AdBlue lockable filler cap 1 pc.
309AA		Beam throw regulator
310CN		High beam headlights and fog lights, also with cornering light
310EE		Halogen twin headlights H7 for right-hand traffic
310HB		Daytime driving Lights (ECE RB7 compliant)
311AA		protective grille for headlights
311CH		off-road logic for ABS
318AA		marker lamps
318AK		lateral marker lights
319AA		reading lamps for driver and co-driver
321EC		central locking
324AC		Two-tone horn. electric
325AA		MAN Tronic (on-board computer)
325EX		Language 1 'Rumanian' for display instrument panel
326CK		trailer socket for anti-skid system on frame end
326FZ		socket in cab 12V 2-pole and 24V 2-pole
326XY		Without 12/24 V socket on end of frame
327AF	X	battery main switch, mechanical
329CW	X	Two 12-V 225-Ah batteries
329ES		Battery box up to 225 Ah
329HC		Maintenance sign for batteries.- 'maintenance-free'
33VAC		engine capsule
331CY		28V three-phase alternator 120A 3360W Longlife Eco
339FP		Display on the dashboard for operating data
343AN		Acoustic warning system at end of frame for engaged reverse gear
345AT		speed limiter electronic 110 km/h
345EA		cruise control
346CA		charging pressure indicator
350IW		Connectivity Board module (RIO Box)
350NN		MAN Media Truck radio, 12V with five-inch colour display
350XO		Without navigation SD
351US		AUX-IN/USB in the instrument panel
362AA		Stabilizer for rear axle
363AA		Stabilizer for front axle
370CR		air dryer, heated
373AE		antifreeze effective down to -35 degrees
376XH		Without Mattress for lower bunk
376XK		Without Mattress for lower bunk
376XL		No bunks for 'M' 'C', 'DK' cabs
380AH		windscreen of laminated glass tinted and heated
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		without curtain before bunks
381YX		without all-round curtain
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post

386XA		without lifting roof
387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390CT		cup holder in dashboard
390XX		without oddment box
392AH		kerb mirror, right
392CL		EU front mirror on co-driver's side
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
400AH		mudflap front
401AF		temporary transport mudguards
401CW		deletion of plastic mudguards
404XG		without spray reduction facility
405AC		Bonding sat, separata
405AK		hazard-warning sign
405AR		hazard-warning lamp
405CP		20 m tyre inflator hose with pressure gauge
407AH		jack 12 t
411AA		1 chock
434DA		interior design in Sand
523AC		signs in English
538AE		plastic floor and engine tunnel covering
542BC		COP document
542BK		exhaust gas certificate Euronorm
542BX		CEMT certification
542DE		Confirmation of conformity to EC Directives
542DM		Supplier declaration
542DP		Confirmation of year of manufacture
542DT		Body manufacturer information sheet
542FB		Anti-noise package 82 dB (92/97EEC) off-road
542IZ		confirmation for international registration
542NG		Registration as an N3G Vehicle, (GW »12 t)
600AC		Fittings for right-hand traffic
798LF		Height over cab, unloaded up to 4000mm
798RA		Body mounting/conversion in acc. with Truck Request. TR number: R1.18035.5386
LQA02		wheels acryl
LQA08		steel bumper in 2-pack acrylic
LQA12		entries acryl
LQA46		mudguards behind cab in 2-pack acrylic
LQW01		chassis in water-based paint
LVS01		Chassis graphite black RAL 9011 matt
LVS02		wheels FLAME RED RAL 3000
LVS03		cab FLAME RED RAL 3000
LVS08		bumper FLAME RED RAL 3000
LVS12		entries FLAME RED RAL 3000
LVS46		mudguards behind cab FLAME RED RAL 3000
80001		2 Continental 14.00R20 HCS TL
90001		2 Continental 14.00R20 HCS TL

Weights:

Gross Weight 18000

1st front axle: 9000

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 10000

2nd rear axle: 0

Trailing axle: 0

The prescribed data corresponds to current manufacturing regulations at the time of expression subject to change.